

G-160 S

G-160 Gravity Enduro Suspension - 160mm

SRP £2,499



Colour	Matt Lime with Black/Magenta
Sizes Available	S, M, L
Frame	6061 T6 SCR Aluminium Front Triangle with Tapered Head Tube and Intergrip integrated seat clamp, ISCG 5 guide mounts, alloy symmetrical SCR rear Triangle, 148mm Boost Dropouts
Fork	RockShox Yari RC, 27.5", 160mm Travel, Fast Black coating, tapered steerer and 110mm X 15mm Boost Maxle
Rear Shock	RockShox Monarch Debonair R, Fast Black coating, Adjustable Rebound and Compression
Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Cartridge Upper Bearing
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub 12mm X 148mm Boost Through Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub 15mm x 110mm Boost Through Axle, 32 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless Steel Spokes
Rims	WTB STs i29 Rims with TCS System, Sleeve Joint, Tubeless Ready
Tyres	WTB Convict TCS Light High Grip 27.5 X 2.5" Folding Front, WTB Riddler TCS Light Fast Rolling 27.5" X 2.4" Folding Rear
Shift Levers	SRAM GX, MMX Clamp, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM GX, 11 Speed Alloy
Cassette	SRAM XG-1150 10-42, 11 Speed
Chain	SRAM PC-1110, 11 Speed
Crankset	SRAM Descendant GXP, XSYNC direct mount 30T chainring, 11 Speed Alloy
Bottom Bracket	SRAM GXP Team, 73mm
Seatpost	RockShox Reverb Stealth 125/150/170mm, 30.9mm, MMX
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Custom Alloy, 35mm Bar Bore, 15mm Rise, 780mm Wide
Stem	Whyte Gravity Stem, 40mm
Grips	Whyte Lock-on
Front Brakes	SRAM Guide R, 4 Pots, 180mm Rotor
Rear Brakes	SRAM Guide R, 4 Pots, 180mm Rotor, Internal Routing
Brake Levers	SRAM Guide R, MMX Matchmaker
Pedals	None

The G-160 S features the very latest Whyte thinking on geometry. With a super short stem and wide bar, the rider can exploit every ounce of performance from the bike.

The S is loaded with the very latest developments in Enduro/Trail bikes, WTB i29mm rims combined with TCS front and rear specific tyres help to give neutral handling without too much drag. SRAM improves both stiffness and gear tuning with their direct mount XSYNC system chain rings, allowing the rider to change ratios easily to suit their terrain.

This bike is ready for anything you want to throw at it, from hard-core trail riding to Enduro racing. Full complement bearings are used throughout the design, giving this bike exceptional durability in the harshest UK conditions.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	63mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	22mm x 8mm, no hardware at the rear
Eye to Eye Length	216mm
Weight	14.4Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.0+0/-1	74.7	607.6	340.5	805.5
M	66.0+0/-1	74.5	636.6	340.5	813.5
L	66.0+0/-1	74.3	655.9	340.5	820.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1181.7	425	30.9	95	406.4
M	1211.7	425	30.9	110	431.8
L	1231.7	425	30.9	120	457.2

G-160 RS

G-160 Gravity Enduro Suspension - 160mm

SRP £3,200



		Colour	Matt Granite with Orange/Grey
		Sizes Available	S, M, L
		Frame	6061 T6 SCR Aluminium Front Triangle with Tapered Head Tube and Intergrip integrated seat clamp, ISCG 5 guide mounts, alloy symmetrical SCR rear Triangle, 148mm Boost Dropouts
✓	✓	Fork	RockShox Lyrik RC, 27.5", 160mm Travel, Fast Black coating, tapered steerer and 110mm X 15mm Boost Maxle
	✓	Rear Shock	RockShox Monarch Debonair, RT3, Fast Black coating, Adjustable Rebound and Compression
		Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Cartridge Upper Bearing
✓	✓	Rear Hub	Whyte Cartridge sealed bearing, 12mm X 148mm Boost Through Axle with Micro Engagement 6 Pawl XD Driver Free Hub, 32 Hole
		Front Hub	Alloy, Double Sealed Cartridge Bearing Hub 15mm x 110mm Boost Through Axle, 32 Hole
		Spokes	WTB 2.0mm, Black Sandvik Stainless Steel Spokes
✓		Rims	WTB STs i29 Rims with TCS System, Sleeve Joint, Tubeless Ready
✓	✓	Tyres	Maxxis High Roller II TR, 27.5" X 2.4" 60TPI 3C(Maxx Terra) Folding Bead, EXO Sidewall protection Front, Maxxis Minion SS, 27.5" X 2.3" 60TPI Dual TLR, Folding Bead, EXO Sidewall protection Rear
✓	✓	Shift Levers	SRAM XO1 Eagle, MMX Clamp, 12 Speed
		Front Derailleur	N/A
✓	✓	Rear Derailleur	SRAM XO1 Eagle, 12 Speed
✓	✓	Cassette	SRAM XG-1295 Eagle 10-50, 12 Speed
✓	✓	Chain	SRAM XX1 Eagle, Black, 12 Speed
✓	✓	Crankset	SRAM Decendent Eagle GXP, XSYNC 2 direct mount 32T chainring, 12 Speed, Carbon
		Bottom Bracket	SRAM GXP Team, 73mm
✓		Seatpost	RockShox Reverb Stealth 125/150/170mm, 30.9mm, MMX
		Seat	Whyte Custom dual density, triple panel design
		Bar	Whyte Custom Alloy, 35mm bar bore, 15mm Rise, 780mm Wide
		Stem	Whyte Gravity Stem, 40mm
		Grips	Whyte Lock-on
		Front Brakes	SRAM Guide R, 4 Pots, 180mm Rotor
		Rear Brakes	SRAM Guide R, 4 Pots, 180mm Rotor, Internal Routing
		Brake Levers	SRAM Guide R, MMX Matchmaker
		Pedals	None

The G-160 RS features SRAM's all new Eagle 12 speed drive-train. With its huge 10-50 gear range, it gives the rider all the climbing and trail riding gears needed to save enough energy for more fun on the way back down.

The RS is loaded with the very latest developments in Trail/Enduro bikes, WTB i29mm rims combined with Maxxis TR front and rear specific tyres help to give neutral handling without too much drag. RockShox suspension gives the rider the very best enduro package available.

This bike is ready for anything you want to throw at it, from hard-core trail riding to Enduro racing. Full complement bearings are used throughout the design, giving this bike exceptional durability in the harshest UK conditions.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	63mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	22mm x 8mm, no hardware at the rear
Eye to Eye Length	216mm
Weight	14.3Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.0+0/-1	74.7	607.6	340.5	805.5
M	66.0+0/-1	74.5	636.6	340.5	813.5
L	66.0+0/-1	74.3	655.9	340.5	820.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1181.7	425	30.9	95	406.4
M	1211.7	425	30.9	110	431.8
L	1231.7	425	30.9	120	457.2

G-160 WORKS

G-160 Gravity Enduro Suspension - 160mm

SRP £4,799



		Colour	Matt Burnt Orange with Black/Blue
		Sizes Available	S, M, L
		Frame	6061 T6 SCR Aluminium Front Triangle with Tapered Head Tube and Intergrip integrated seat clamp, ISCG 5 guide mounts, alloy symmetrical SCR rear Triangle, 148mm Boost Dropouts
✓	✓	Fork	RockShox Lyrik, RCT3, 27.5", 160mm Travel, Fast Black coating, tapered steerer and 110mm X 15mm Boost Maxle
	✓	Rear Shock	RockShox Monarch Plus Debonair, RC3, Fast Black coating, Adjustable Rebound and Compression
		Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Cartridge Upper Bearing
✓	✓	Rear Hub	SRAM Roam 60, 12 x 148mm Boost Through Axle
✓	✓	Front Hub	SRAM Roam 60, 15 x 110mm Boost Through Axle
✓	✓	Spokes	SRAM Roam 60, StSt Butted
✓	✓	Rims	SRAM Roam 60, 30mm wide carbon Hookless rims, Full UST Rims
		Tyres	Maxxis High Roller II TR, 27.5" X 2.4" 60TPI 3C(Maxx Terra) Folding Bead, EXO Sidewall protection Front, Maxxis Minion SS, 27.5" X 2.3" 60TPI Dual TLR, Folding Bead, EXO Sidewall protection Rear
✓		Shift Levers	SRAM XO1 Eagle, MMX Clamp, 12 Speed
		Front Derailleur	N/A
✓		Rear Derailleur	SRAM XO1 Eagle, 12 Speed
✓		Cassette	SRAM XG-1295 10-50, 12 Speed
✓		Chain	SRAM XX1 Eagle, Black, 12 Speed
✓	✓	Crankset	SRAM XO1 Eagle GXP, XSYNC direct mount 34T Chainring, 12 Speed Carbon
		Bottom Bracket	SRAM GXP Team, 73mm
✓		Seatpost	RockShox Reverb Stealth 125/150/170mm, 30.9mm, MMX
		Seat	Whyte Custom dual density, triple panel design
	✓	Bar	RaceFace SIXC Carbon 35mm Oversize, 20mm rise, 800mm wide
✓	✓	Stem	RaceFace Turbine 35mm Oversize, 32mm long
		Grips	Whyte Lock-on
	✓	Front Brakes	SRAM Guide RSC, 4 Pots, 200mm Rotor
	✓	Rear Brakes	SRAM Guide RSC, 4 Pots, 180mm Rotor, Internal Routing
	✓	Brake Levers	SRAM Guide RSC MMX Matchmaker
		Pedals	None

This is the bike our Gravity Enduro Team race on, and as such, it's got the best of everything, from SRAM, RockShox, RaceFace, Maxxis, and of course, Whyte.

This bike is ready for anything you want to throw at it, from hard-core trail riding to EWS Enduro racing. Full complement bearings are used throughout the design, giving this bike exceptional durability in the harshest UK conditions.

The 2017 frame geometry progresses even further as our Race Team experience is back-fed into our development programme.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	63mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	22mm x 8mm, no hardware at the rear
Eye to Eye Length	216mm
Weight	13.5Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.0+0/-1	74.7	607.6	340.5	805.5
M	66.0+0/-1	74.5	636.6	340.5	813.5
L	66.0+0/-1	74.3	655.9	340.5	820.5

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1181.7	425	30.9	95	406.4
M	1211.7	425	30.9	110	431.8
L	1231.7	425	30.9	120	457.2

T-130 SX

T-130 Trail/Enduro Suspension - 130mm

SRP £1,999



Colour	Magenta with Black/Lime
Sizes Available	XS,S,M,L
Frame	6061 T6 SCR Aluminium SCR Front Triangle with Tapered Head Tube and Intergrip integrated seat clamp system, alloy symmetrical SCS rear Triangle, 148mm Boost dropouts, Shimano Direct Mount hanger
Fork	SR Suntour Aion LO-R 27.5" CTS, Air Spring, 130mm Travel, Tapered steerer and 15QR
Rear Shock	Fox Float DPS Performance, Black coating, Rebound Adjustment and 3pos Adjust Evol
Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Upper Bearing
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 12mm X 148mm Boost Through Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub 15mm X 100mm Through Axle, 32 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless Steel Spokes, Brass Nipples
Rims	WTB STp i29 TCS System, Tubeless Ready, 32 Hole
Tyres	WTB Trail Boss, TCS Light High Grip 27.5" X 2.25", 60TPI, Folding Front, Riddler, Light Fast Rolling TCS 27.5" X 2.25", 60TPI, Folding Rear
Shift Levers	Shimano SLX M7000, I-Spec B, 11 Speed, Black
Front Derailleur	N/A
Rear Derailleur	Shimano SLX M7000, Shadow Plus, 11 Speed, Direct Mount
Cassette	SRAM PG-1130 11-42, 11 Speed
Chain	Shimano HG60, 11 Speed
Crankset	RaceFace Affect, direct mount 28T, 11 Speed
Bottom Bracket	RaceFace BSA, 73mm
Seatpost	KS LEV-Integra, Dropper Post with KG remote, 30.9, 100mm travel
Seat	Whyte Custom, dual density, triple panel design
Bar	Whyte Custom Alloy, 15mm Rise, 760mm Wide
Stem	Whyte Gravity Stem, 40mm XS/S, 50mm M/L
Grips	Whyte Lock-on
Front Brakes	TRP Slate T4, Four Pot, I-spec, 180mm Rotor
Rear Brakes	TRP Slate T4, Four Pot, I-spec, 160mm Rotor, Internal Routing
Brake Levers	TRP Slate, I-Spec
Pedals	None

The T-130SX gets a huge upgrade for 2017 and now uses the SCR single chainring specific frame. This multi-award winning frame is combined with the new SLX M7000 series 1 by 11 group set from Shimano.

WTB STp i29 rims and TCS tyres give a Tubeless ready wheelset which, when combined with the SR Aion fork and Fox Float DPS double chamber rear shock, give the SX the ability to tame your favourite trails.

Internal routing keeps cables and hoses out of harm's way and with our new rubberised frame grommets it's totally water tight.

Dropout Code	DROPWHQ4SD
Shock Stroke and Sag Setting	63mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	216mm
Weight	14.2Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	67.0 +0/-1	74	571.7	331	761
S	67.0 +0/-1	73.7	581.4	331	763
M	67.0 +0/-1	73.5	611.1	331	766
L	67.0 +0/-1	73.3	631	331	776

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1116.5	420	30.9	100	368.3
S	1136.5	420	30.9	107	406.4
M	1156.5	420	30.9	115	431.8
L	1176.5	420	30.9	120	457.2

T-130S

T-130 Trail/Enduro Suspension - 130mm

SRP £2,450



Colour	Matt Orange with Black/Blue
Sizes Available	XS,S,M,L,XL
Frame	6061 T6 SCR Aluminium Front Triangle with Tapered Head Tube and Intergrip integrated seat clamp system, alloy symmetrical SCR rear Triangle, 148mm Boost dropouts
Fork	RockShox Yari 27.5", RL, 130mm Travel, Fast Black coating, Tapered steerer and 110mm X 15mm Boost Maxle
Rear Shock	RockShox Monarch Debonair, RT, Fast Black coating, Adjustable Rebound and Compression
Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Upper Bearing
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 12mm X 148mm Boost Through Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub Hub 15mm X 110mm Boost Through Axle, 32 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless Steel Spokes, Brass Nipples
Rims	WTB STs i29, 29mm wide, Sleeved Joint, TCS Rims
Tyres	WTB Vigilante, Light High Grip TCS 27.5" X 2.3", 60TPI Folding Front, Trail Boss, TCS Light Fast Rolling 27.5" X 2.4", 60TPI Folding Rear
Shift Levers	SRAM GX MMX Clamp, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM GX, 11 Speed
Cassette	SRAM PG-1150 10-42, 11 Speed
Chain	SRAM PC-1110, 11 Speed
Crankset	SRAM GX, XSYNC direct mount 30T, Boost 11 Speed
Bottom Bracket	SRAM GXP, 73mm
Seatpost	RockShox Reverb Stealth 125/150mm, 30.9mm, MMX
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Custom Alloy, 15mm Rise, 760mm Wide
Stem	Whyte Gravity Stem, 40mm S/M, 50mm L/XL
Grips	Whyte Lock-on
Front Brakes	SRAM Level TL, 180mm Rotor
Rear Brakes	SRAM Level TL, 160mm Rotor, Internal Routing
Brake Levers	SRAM Level TL, MMX Matchmaker
Pedals	None

The T-130 S features our SCR single ring specific frame with mega stiff symmetrical chainstays. A full width main pivot increases torsional stiffness, extends bearing life and maximises suspension performance.

The geometry of the T-130 has been adjusted to accommodate a shorter stem giving the bike some of the most progressive trail geometry available today.

A low slung shock gives the T-130 plenty of stand-over height and suspension kinematics that make the bike really "pump" through your favourite singletrack.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	63mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	216mm
Weight	14.2Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	67.0 +0/-1	74	571.7	331	761
S	67.0 +0/-1	73.7	581.4	331	763
M	67.0 +0/-1	73.5	611.1	331	766
L	67.0 +0/-1	73.3	631	331	776
XL	67.0 +0/-1	73.2	650.7	331	786

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1116.5	420	30.9	100	368.3
S	1136.5	420	30.9	107	406.4
M	1156.5	420	30.9	115	431.8
L	1176.5	420	30.9	120	457.2
XL	1196.5	420	30.9	130	482.6

T-130 RS

T-130 Trail/Enduro Suspension - 130mm

SRP £2,950



Colour	Matt Granite with Lime/Magenta
Sizes Available	S, M, L, XL
Frame	6061 T6 SCR Aluminium SCR Front Triangle with Tapered Head Tube and Intergrip integrated seat clamp system, alloy symmetrical SCS rear Triangle, 148mm Boost dropouts, Shimano Direct Mount hanger
Fork	Fox Float Performance 34, 27.5", 130mm Travel with GRIP 3-Pos Damper, Tapered steerer, Black Coating and 110mm x 15mm Boost E-Thru Axle
Rear Shock	Fox Float DPS Performance, Black coating, Rebound Adjustment and 3pos Adjust Evol
Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Upper Bearing
Rear Hub	Hope Pro 4 with StSt Bearings, 11 Speed Shimano Freehub, 12mm X 148mm Boost Through Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub Hub 15mm X 110mm Boost Through Axle, 32 Hole
Spokes	DT Champion 2.0mm
Rims	WTB STs i29, 29mm wide, Sleeved Joint, TCS Rims
Tyres	WTB Vigilante, Light High Grip TCS 27.5" X 2.3", 60TPI Folding Front, Trail Boss, TCS Light Fast Rolling 27.5" X 2.4", 60TPI Folding Rear
Shift Levers	Shimano XT M8000, I-spec II, 11 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano XT M8000, 11 Speed, Shadow Plus, Direct Mount
Cassette	Shimano XT M8000 11-46, 11 Speed
Chain	Shimano XT HG600, 11 Speed
Crankset	RaceFace Turbine Clinch, direct mount 32T chainring, 11 Speed, 30mm alloy Boost axle
Bottom Bracket	RaceFace BSA, 73mm
Seatpost	RockShox Reverb Stealth 125/150mm, 30.9mm
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Custom Alloy, 15mm Rise, 760mm Wide
Stem	Whyte Gravity Stem, 40mm S, 50mm M/L/XL
Grips	Whyte Lock-on
Front Brakes	Shimano XT M8000, 180mm Rotor
Rear Brakes	Shimano XT M8000, 160mm Rotor, Internal Routing
Brake Levers	Shimano XT M8000, I-spec II
Pedals	None

The T-130 RS features our SCR single ring specific frame with mega-stiff symmetrical chainstays. A full width main pivot increases torsional stiffness, extends bearing life and maximises suspension performance.

The T-130 RS beat all comers in the prestigious "2016 Trail Bike of the Year" award in the What Mountain Bike, and for 2017 this bike sees improvements in both the wheels and suspension, keeping it in front of the crowd.

Whyte hubs are laced to WTB STs i29 29mm wide rims with WTB high air volume tyres to allow you to exploit even more speed and fun out of the T-130's geometry. Suspension is handled by Fox, using Boost lowers and their all-new GRIP damper which brings World Cup winning suspension performance to the T-130 RS.

Dropout Code	DROPWHQ4SD
Shock Stroke and Sag Setting	63mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	216mm
Weight	13.7Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	67.0 +0/-1	73.7	581.4	331	763
M	67.0 +0/-1	73.5	611.1	331	766
L	67.0 +0/-1	73.3	631	331	776
XL	67.0 +0/-1	73.2	650.7	331	786

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1136.5	420	30.9	107	406.4
M	1156.5	420	30.9	115	431.8
L	1176.5	420	30.9	120	457.2
XL	1196.5	420	30.9	130	482.6

T-130C RS

T-130 Trail/Enduro Suspension - 130mm

SRP £3,799



Colour	Granite with Orange/Blue
Sizes Available	M, L, XL
Frame	Uni-directional Multi Monocoque Front Triangle with internal cable routing, Tapered Head Tube and Intergrip integrated seat clamp system with alloy symmetrical SCR rear Triangle, 148mm Boost Dropouts
Fork	RockShox Pike RC, 27.5", 130mm Travel, Fast Black coating, tapered steerer and 10mm X 15mm Boost Maxle
Rear Shock	RockShox Monarch Debonair, RT3, Fast Black coating, Adjustable Rebound and Compression
Headset	FSA No. 42 Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings
Rear Hub	Whyte Cartridge sealed bearing, 12mm X 148mm Boost Through Axle with Micro Engagement 6 Pawl XD Driver Free Hub, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub 15mm x 110mm Boost Through Axle, 32 Hole
Spokes	DT Swiss Champion 2.0mm
Rims	RaceFace ARC-30, 30mm wide, Welded Joint, tubeless ready
Tyres	Maxxis High Roller II TR, 27.5" X 2.3" 60TPI 3C(Maxx Terra) Folding Bead, EXO Sidewall protection Front, Maxxis Crossmark II TR 27.5 X 2.2" EXO Sidewall protection, Folding Rear
Shift Levers	SRAM X01 Eagle, MMX Clamp, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM X01 Eagle, 12 Speed
Cassette	SRAM XG-1295 Eagle 10-50, 12 Speed
Chain	SRAM XX1 Eagle, Black, 12 Speed
Crankset	SRAM X1-1400 Eagle GXP, XSYNC 2 Direct Mount 34T Boost chainring, 12 Speed Alloy
Bottom Bracket	SRAM GXP Team, 73mm
Seatpost	RockShox Reverb Stealth 125/150mm, 30.9mm, MMX
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Custom Alloy, 15mm Rise, 760mm Wide
Stem	Whyte Gravity Stem, 40mm M, 50mm L/XL
Grips	Whyte Lock-on
Front Brakes	SRAM Guide RS, 4 Pots, 180mm Rotor
Rear Brakes	SRAM Guide RS, 4 Pots, 160mm Rotor, Internal Routing
Brake Levers	SRAM Guide RS, MMX Matchmaker
Pedals	None

The T-130 C RS features our single ring specific Carbon frame. A full width main pivot that increases torsional stiffness, extends bearing life and maximises suspension performance.

SRAM's all-new Eagle X01 12 speed drive-train is used on the T-130 C RS. This evolutionary groupset gives a massive 10-50 gear spread cassette, allowing the chainring to be increased to 34t, giving both top and bottom range improvement.

RaceFace ARC-30, 30mm wide, welded joint, UST Tubeless rims are combined with Maxxis TR tyres to give exceptional levels of control. Boost 148mm rear and 110mm front hubs have 10mm wide flange spacing creating a stiffer wheel.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	63mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	216mm
Weight	13.2Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	67.0 +0/-1	73.5	611.1	331	766
L	67.0 +0/-1	73.3	631	331	776
XL	67.0 +0/-1	73.2	650.7	331	786
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1156.5	420	30.9	115	431.8
L	1176.5	420	30.9	120	457.2
XL	1196.5	420	30.9	130	482.6

T-130C WORKS

T-130 Trail/Enduro Suspension - 130mm

SRP £4,999



Colour	Matt Orange with Black/Blue
Sizes Available	M, L, XL
Frame	Uni-directional Multi Monocoque Front Triangle with internal cable routing, Tapered Head Tube and Intergrip seat clamp with alloy symmetrical SCR rear Triangle, 148mm Boost Dropouts
Fork	RockShox Pike RCT-3, 27.5", 130mm Travel, Fast Black coating, tapered steerer and Boost 15mm X 110mm Maxle
Rear Shock	RockShox Monarch Debonair, RT3, Fast Black coating, Adjustable Rebound and Compression
Headset	FSA No. 42 Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings
Rear Hub	Whyte Cartridge sealed bearing, 12mm X 148mm Boost Through Axle with Micro Engagement 6 Pawl XD Driver Free Hub, 28 Hole
Front Hub	Whyte Cartridge sealed Bearing, 15mm x 110mm Boost Through Axle, 28 Hole
Spokes	DT Comp RACE 2.0mm with 14mm Brass Nipples
Rims	Whyte 30mm Carbon Hookless, 28H, Tubeless Ready, 3M Rim strip with Tubeless valves included
Tyres	Maxxis High Roller II TR, 27.5" X 2.3" 60TPI 3C(Maxx Terra) Folding Bead, EXO Sidewall protection Front, Maxxis Crossmark II TR 27.5 X 2.2" EXO Sidewall protection, Folding Rear
Shift Levers	SRAM XX1 Eagle, MMX Clamp, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM XX1 Eagle, 12 Speed
Cassette	SRAM XG-1295 Eagle 10-50, 12 Speed
Chain	SRAM XX1 Eagle, Black, 12 Speed
Crankset	SRAM XX1 Eagle GXP, XSYNC 2 34T Direct Mount Boost chainring, 12 Speed Alloy
Bottom Bracket	SRAM GXP Team, 73mm
Seatpost	RockShox Reverb Stealth 125/150mm, 30.9mm, MMX
Seat	Whyte Custom dual density, triple panel design
Bar	RaceFace SIXC Carbon, 760mm wide, 20mm rise
Stem	Whyte Gravity Stem, 40mm M, 50mm L/XL
Grips	Whyte Lock-on
Front Brakes	SRAM Guide RSC, 4 Pots, 180mm Rotor
Rear Brakes	SRAM Guide RSC, 4 Pots, 160mm Rotor, Internal Routing
Brake Levers	SRAM Guide RSC, MMX Matchmaker
Pedals	None

The T-130 C Works features our single ring specific Carbon frame. A full width main pivot that increases torsional stiffness, extends bearing life and maximises suspension performance.

SRAM's all new Eagle XX1 drive-train is used on the T-130 C Works. This evolutionary groupset gives a massive 10-50 gear spread cassette allowing the chainring to be increased to 34t, giving both top and bottom range improvement.

The Works comes with Whyte's own 30mm wide hookless carbon tubeless ready rims laced onto our own hubs with DT Swiss spokes and brass nipples. This build gives both lightweight and security when pushing the Works to the limit.

Dropout Code	DROPWHQ4SD
Shock Stroke and Sag Setting	63mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	216mm
Weight	12.9Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	67.0 +0/-1	73.5	611.1	331	766
L	67.0 +0/-1	73.3	631	331	776
XL	67.0 +0/-1	73.2	650.7	331	786
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1156.5	420	30.9	115	431.8
L	1176.5	420	30.9	120	457.2
XL	1196.5	420	30.9	130	482.6

901

Trail / Enduro Hardtail - 900 Series - 130mm

SRP £1,199



Colour	Matt Lime with Black/Denim
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted, Tapered Headtube, Get A Grip seat clamp system with Internal BBX Cable routing for Dropper Post and 12mm X 148mm Boost Dropouts
Fork	RockShox Sektor Gold 27.5" Lock-out, 130mm Travel, Fast Black coating, Solo Air, Adjustable Compression and Rebound, Tapered Steerer, 100mm X 15mm, Maxle
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, Sealed Cartridge Bearing 1.5" Lower, 1 1.8" Caged Upper Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 12mm X 148mm Boost Through Axle, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 15mm Through Axle, 32 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless with Brass Nipples
Rims	WTB STp i29 TCS System, Tubeless Ready, 32 Hole
Tyres	WTB Trail Boss, Light High Grip TCS 27.5" X 2.4", 60TPI Folding Front, Riddler Fast Light Rolling TCS 27.5" X 2.4" TCS, 60TPI Folding Rear
Shift Levers	SRAM NX, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM NX, 11 Speed
Cassette	SRAM PG-1130, 11-42, 11 Speed
Chain	SRAM PC-1110, 11 Speed
Crankset	SRAM NX, XSYNC direct mount 32T, Boost 11 Speed
Bottom Bracket	SRAM GXP, 73mm
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Custom 6061 Alloy, Low Rise, 760mm Wide
Stem	Whyte Gravity Stem, 40mm S/M, 50mm L/XL
Grips	Whyte Custom Lock-on
Front Brakes	SRAM Level, 180mm Rotor
Rear Brakes	SRAM Level, 160mm Rotor, Internal Routing
Brake Levers	SRAM Level
Pedals	None

With the 901, it's all about the geometry - it will make you feel more confident in all situations than any hardtail you've ever ridden. For 2017 we have an all new 1 by specific frame, with a 12mm bolt through Boost rear axle, giving extra stiffness and increased chain clearance.

The award winning 901 features the "Get A Grip" seat post clamp system. This allows quick adjustment, fantastic weather proofing and a nice ergonomic lever which is easy to operate however cold your hands might be.

Awarding a magnificent 10/10 MBR describes the 901 as "everything a great trail hardtail should be".

Dropout Code	DROPWH17
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	12.2Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.5	73	618.7	305	778
M	66.5	73	637.5	305	794
L	66.5	73	655.1	305	816
XL	66.5	73	674	305	833

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1138.8	425	30.9	110	406.2
M	1168.8	425	30.9	120	431
L	1178.8	425	30.9	140	457.2
XL	1203.8	430	30.9	150	482.6

905

Trail / Enduro Hardtail - 900 Series - 130mm

SRP £1,699



Colour	Matt Orange with Black/Blue
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted, Tapered Headtube, Intergrip integrated seat clamp system with Internal BBX Cable routing for Dropper Post and 12mm X 148mm Boost Dropouts
Fork	RockShox Yari 27.5", RL, 130mm Travel, Fast Black coating, Tapered steerer and 110mm X 15mm Boost, Maxle
Rear Shock	N/A
Headset	FSA No. 57E Orbit ZS, Sealed Cartridge Bearings, 1.5" Lower, 1 1.8" Upper Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 12mm X 148mm Boost Through Axle, 32 Hole
Front Hub	Alloy, Double Sealed, Cartridge Bearing Hub, 15mm X 110mm Boost Through Axle, 32 Hole
Spokes	DT Champion 2.0mm Black Stainless with Brass Nipples
Rims	WTB STp i29 TCS System, Tubeless Ready, 32 Hole
Tyres	WTB Trail Boss, Ligh High Grip TCS 27.5" X 2.4", 60TPI Folding Front, Riddler Fast Light Rolling TCS 27.5" X 2.4" TCS, 60TPI Folding Rear
Shift Levers	SRAM GX, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM GX, 11 Speed
Cassette	SRAM PG-1150 10-42, 11 Speed
Chain	SRAM PC-1110, 11 Speed
Crankset	SRAM GX, XSYNC direct mount 32T, Boost 11 Speed
Bottom Bracket	SRAM GXP, 73mm
Seatpost	JD Dropper Post with under bar remote, 30.9mm X 420mm, 125mm travel
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Custom Alloy, Low Rise, 760mm Wide
Stem	Whyte Gravity Stem, 40mm S/M, 50mm L/XL
Grips	Whyte Custom Lock-on
Front Brakes	SRAM Level T, 180mm Rotor
Rear Brakes	SRAM Level T, 160mm Rotor, Internal Routing
Brake Levers	SRAM Level T, Matchmaker
Pedals	None

The award winning 905 is back and better than ever for 2017, with a dropper post, SRAM GX 1 by 11 and WTB wide rims with high air volume TCS tyres. All these features give the rider even more "Trail Control".

The 905 has an all new frame for 2017 with "Intergrip" seat post clamp system, new BBX internal cable routing and 12mm bolt through Boost rear axle, giving extra stiffness and increased chain clearance.

WTB STp i29 29mm wide TCS rims combined with 2.4" high volume TCS Tubeless tyres give the 2017 905 more grip so the rider can push the bike even harder. To give extra front end grip we have specced a High-Grip compound tyre.

Dropout Code	DROPWH17
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	12.3Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.5	73	618.7	305	767
M	66.5	73	637.5	305	795
L	66.5	73	655.1	305	822
XL	66.5	73	673.9	305	851

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1138.8	425	30.9	110	406.2
M	1168.8	425	30.9	120	431
L	1178.8	425	30.9	140	457.2
XL	1203.8	430	30.9	150	482.6

909

Trail / Enduro Hardtail - 900 Series - 130mm

SRP £2,150



Colour	Matt Granite with Grey/Gold
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted, Tapered Headtube, Intergrip integrated seat clamp system with Internal BBX Cable routing for Dropper Post and 12mm X 148mm Boost Dropouts
Fork	Fox Float Performance 34, 27.5", 130mm Travel with GRIP 3-Pos Damper, Tapered steerer, Black Coating and 110mm X 15mm Boost, E-Thru Axle
Rear Shock	N/A
Headset	FSA No. 57E Orbit ZS, Sealed Cartridge Bearings, 1.5" Lower, 1 1/8" Upper Bearings
Rear Hub	Hope PRO4 with StSt Bearings, 12mm X 148mm Boost Through Axle, 11 Speed Shimano Freehub, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 15mm X 110mm Boost Through Axle, 32 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless with Brass Nipples
Rims	WTB STs i29 Rims with TCS System, Sleeve Joint, Tubeless Ready
Tyres	WTB Trail Boss, Light High Grip TCS 27.5" X 2.4", 60TPI Folding Front, Riddler Fast Light Rolling TCS 27.5" X 2.4" TCS, 60TPI Folding Rear
Shift Levers	Shimano XT M8000 I-spec II, 11 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano XT M8000, 11 Speed, Shadow Plus, Direct Mount
Cassette	Shimano XT M8000, 11-46, 11 Speed
Chain	Shimano HG-601, 11 Speed
Crankset	RaceFace Turbine, direct mount 32T chainring, 11 Speed, with 30mm alloy Boost axle
Bottom Bracket	RaceFace BSA, 73mm
Seatpost	KS CRUXi Dropper Post with Southpaw-Alloy remote, 30.9mm X 425mm, 125mm travel
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Custom Alloy, Low Rise, 760mm Wide
Stem	Whyte Gravity Stem, 40mm S/M, 50mm L/XL
Grips	Whyte Custom Lock-on
Front Brakes	Shimano XT M8000, 180mm Rotor
Rear Brakes	Shimano XT M8000, 160mm Rotor, Internal Routing
Brake Levers	Shimano XT M8000, I-Spec II
Pedals	None

Our top-end trail hardtail is dripping with lust-worthy components such as Shimano's XT M8000 1 by 11 groupset and brakes, RaceFace's Turbine Clinch direct mount chainset system with a 30mm alloy Boost axle and screw in BSA BB cups.

For 2017 the 909 gets full-on Enduro/Trail attitude with the all new Fox 34 fork, with its GRIP damper, which gives amazing steering precision and poise when combined with Whyte's trail geometry.

The 909 has an all new frame for 2017 with "Intergrip" seat post clamp system, new BBX internal cable routing and 12mm bolt through 148mm Boost rear axle, giving extra stiffness and increased chain clearance.

Dropout Code	DROPWH17
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	12.6Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.5	73	618.7	305	767
M	66.5	73	637.5	305	795
L	66.5	73	655.1	305	822
XL	66.5	73	673.9	305	851

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1138.8	425	30.9	110	406.2
M	1168.8	425	30.9	120	431
L	1178.8	425	30.9	140	457.2
XL	1203.8	430	30.9	150	482.6

403

Kid's 26er Trail Hardtail - 400 Series - 100mm

SRP £625



Colour	Matt Lime with Denim/Black
Sizes Available	13"
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Get A Grip seat clamp system, Internal Cable routing with BBX, Post Mount Chainstay Dropouts
Fork	Suntour, XCR, 100mm Travel, 32mm, HYDRO Lock-out, Air Spring, Adjustable Rebound, Post Mount
Rear Shock	N/A
Headset	FSA No.10, Semi integrated, Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	Whyte Trail-403, 28 Hole
Tyres	WTB Bronson Race, 26" X 2.1", Front, WTB Riddler, 26" X 1.95", Rear
Shift Levers	Shimano 8-Speed REVO Grip Shifter
Front Derailleur	N/A
Rear Derailleur	Shimano ALTUS
Cassette	Sunrace 8 Speed, ED Black 11-40T
Chain	KMC 8 Speed
Crankset	28T Narrow/Wide Chainring, 165mm Crank Length
Bottom Bracket	TH Sealed, Square Taper, 73mm
Seatpost	Whyte 20mm Offset, 30.9mm x 300mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte Riser Bar 30mm rise DB, 31.8mm, 640mm Wide
Stem	Whyte Custom, 45mm
Grips	Whyte Custom
Front Brakes	Promax Solve, 160mm Rotor
Rear Brakes	Promax Solve, 160mm Rotor, Internal Routing
Brake Levers	Promax Solve, Short Reach
Pedals	Fibre Reinforced Composite Platform

We've broken the mould with our kids bikes. By putting 26" wheels on a kids MTB we've given a boost in performance similar to an adult switching to a 650b/27.5" Trail Hardtail. More confidence, more control and easier riding.

The 403 uses a REVO Shift so small hands can easily exploit the huge range of gears 11-40T.

The 403 also comes with Whyte's own Get-a-Grip seat post clamping system. This easy to use clamp allows the post to be raised or lowered on the trail, even with small cold hands.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	11.4Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
13"	68.5	74	563.3	305	714
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
13"	1076	425	30.9	100	331

405

Kid's 26er Trail Hardtail - 400 Series - 100mm

SRP £999



Colour	Matt Orange with Grey/Blue
Sizes Available	13
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Get A Grip seat clamp system, Internal Cable routing with BBX, Post Mount Chainstay Dropouts
Fork	SR Epixon, 100mm Travel, Alloy Stanchions, Alloy Steerer, Hydro Lockout, Air Spring, Adjustable Rebound
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, Caged Bearings
Rear Hub	Alloy, 4 Cartridge Sealed Bearing, XD Driver, 28 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	Whyte Trail-405, 28 Hole
Tyres	WTB Bronson Race, 26" X 2.1", 60TPI Folding Front, WTB Riddler, 26" X 1.95", Rear
Shift Levers	SRAM GX Gripshift, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM GX, 11 Speed
Cassette	SRAM GX-1150, 10-42, 11 Speed
Chain	SRAM PC-1130, 11 Speed
Crankset	SRAM X1-1000 GXP, XSYNC direct mount 30T chainring, 11 Speed Alloy, 165mm Crank Arms
Bottom Bracket	SRAM GXP, 73mm
Seatpost	Whyte 20mm Offset, 30.9mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte Custom 6061 Alloy, Low Rise, 680mm Wide
Stem	Whyte Gravity, 40mm
Grips	SRAM Lock-On's
Front Brakes	Tektro Auriga, 160mm rotor
Rear Brakes	Tektro Auriga, 160mm rotor, Internal Routing
Brake Levers	Tektro Auriga
Pedals	Fibre Reinforced Composite Platform

We've broken the mould with the 405. By putting 26" wheels on a kids MTB we've given a boost in performance similar to an adult switching to a 650b/27.5" Trail Hardtail. More confidence, more control and easier riding.

With the all new SRAM GX 1 by 11 spec and Gripshift Shifter, small hands can easily exploit the huge range of gears but we haven't stopped there. We have specced a XSYNC Direct Mount chainring so multiple chainrings are available to tune this bike to the local terrain.

The 405 also comes with Whyte's own Get-a-Grip seat post clamping system. This easy to use clamp allows the post to be raised or lowered on the trail, even with small cold hands.

Dropout Code	DROPWH9
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	12.1Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
13"	68.5	74	563.3	305	714
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
13"	1076	425	30.9	100	331

801

Trail Hardtail - 800 Series - 120mm

SRP £820



Colour	Matt Granite with Lime/Grey
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Tapered Headtube, Internal Cable Routing with BBX, Chainstay Post Mount Dropouts and Get A Grip seat clamp system
Fork	RockShox 30 Silver, 120mm Travel, Solo Air, Adjustable Rebound, Alloy Steerer, Turn Key Lockout
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, Sealed Cartridge Bearing 1.5" Lower, 1 1.8" Caged Upper Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
Rims	Whyte Trail-21, sleeve joint, Offset rims, 32 Hole
Tyres	Maxxis Ardent Wire 27.5" x 2.25" Front, Maxxis Crossmark II Wire 27.5" x 2.25" Rear
Shift Levers	Shimano Acera M3000, 9 Speed
Front Derailleur	Shimano Deore M618
Rear Derailleur	Shimano Deore RD-M592 Shadow
Cassette	Shimano HG-200, 11-34, 9 Speed
Chain	Shimano HG-53, 9 Speed
Crankset	SR Suntour XCM, Compact Double 36-22, 9 Speed, 2pcs
Bottom Bracket	SR Suntour, BSA, 73mm
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 Bolt Clamp, Adjuster
Seat	Whyte Custom
Bar	Whyte Riser Bar 15mm rise, 31.8mm, 720mm Wide
Stem	Whyte Custom, 45mm S, M, 60mm L & XL
Grips	Whyte Custom Lock-on
Front Brakes	Tektro Auriga, 160mm rotor
Rear Brakes	Tektro Auriga, 160mm rotor, Internal Routing
Brake Levers	Tektro Auriga
Pedals	Fibre Reinforced Composite Platform

Our range of aluminium hardtails offer a fine balance of fun, control and speed - and the 801 is the perfect entry point with 18 Shimano gears and RockShox 120mm 30 Silver fork with Solo Air.

The 800 Series frame is brand new for 2017, using the very latest Whyte geometry, based around a longer top tube, a short stem and wide 720mm bar. The 800 series bikes are also built around a 120mm travel fork, which brings trail bike levels of performance.

This new frame bristles with UK design features such as the "Get A Grip" seat post clamp system. This allows quick adjustment, fantastic weather proofing and a nice ergonomic lever which is easy to operate however cold your hands might be.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	13.2Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.5	74	604	303.5	789
M	66.5	74	623	303.5	807
L	66.5	74	641	303.5	832
XL	66.5	74	660	303.5	861

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1148	435	30.9	115	406
M	1168	435	30.9	125	444
L	1189	435	30.9	135	482.6
XL	1208	435	30.9	145	533

802 COMPACT-FIT

Trail Hardtail - 800 Series - 120mm

SRP £820



Colour	Magenta with Black/Grape
Sizes Available	XS,S,M
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Tapered Headtube, Internal Cable Routing with BBX, Chainstay Post Mount Dropouts and Get A Grip seat clamp system
Fork	RockShox 30 Silver, 120mm Travel, Solo Air, Adjustable Rebound, Alloy Steerer, Turn Key Lockout
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, Sealed Cartridge Bearing 1.5" Lower, 1 1.8" Caged Upper Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
Rims	Whyte Trail-21, sleeve joint, Offset rims, 32 Hole
Tyres	Maxxis Ardent Wire 27.5" x 2.25" Front, Maxxis Crossmark II Wire 27.5" x 2.25" Rear
Shift Levers	Shimano Acera M3000, 9 Speed
Front Derailleur	Shimano Deore M618
Rear Derailleur	Shimano Deore RD-M592 Shadow
Cassette	Shimano HG-200, 11-34, 9 Speed
Chain	Shimano HG-53, 9 Speed
Crankset	SR Suntour XCM, Compact Double 36-22, 9 Speed, 2pcs
Bottom Bracket	SR Suntour, BSA, 73mm
Seatpost	Whyte 20mm Offset, 30.9mm x 350mm, 6061 Alloy, 2 Bolt Clamp, Adjuster
Seat	Whyte Custom
Bar	Whyte Riser Bar 15mm rise, 31.8mm, 720mm Wide
Stem	Whyte Custom, 45mm
Grips	Whyte Custom Lock-on
Front Brakes	Tektro Auriga, 160mm rotor
Rear Brakes	Tektro Auriga, 160mm rotor, Internal Routing
Brake Levers	Tektro Auriga
Pedals	Fibre Reinforced Composite Platform

The 802 is available in the XS size, and all sizes sport more compact geometry than the 801 or 805. That means slightly less length for more comfortable reach suiting riders with shorter proportions.

The 800 Series frame is brand new for 2017, using the very latest Whyte geometry, based around a longer top tube, a short stem and wide 720mm bar. The 800 series bikes are also built around a 120mm travel fork, which brings trail bike levels of performance.

This new frame bristles with UK design features such as the "Get A Grip" seat post clamp system. This allows quick adjustment, fantastic weather proofing and a nice ergonomic lever which is easy to operate however cold your hands might be.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	13.2Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	66.5	74	580	303.5	786
S	66.5	74	599	303.5	794
M	66.5	74	618	303.5	814
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1123	435	30.9	107	381
S	1143	435	30.9	115	406
M	1163	435	30.9	125	444

805

Trail Hardtail - 800 Series - 120mm

SRP £1,075



Colour	Lime with Black/Denim
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Tapered Headtube, Internal Cable Routing with BBX, Chainstay Post Mount Dropouts and Get A Grip seat clamp system
Fork	RockShox Recon Silver RL, 120mm Travel, Turn Key Lockout with Adjustable Rebound, Tapered Alloy Steerer with 100mm X 15mm Maxle
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, Sealed Cartridge Bearing 1.5" Lower, 1 1.8" Caged Upper Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 15mm X 100mm Through Axle, 32 Hole
Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
Rims	WTB Asym i23 Rims with TCS System, Tubeless Ready, 32 Hole
Tyres	Maxxis Ardent Folding 27.5" x 2.25" Front, Maxxis Crossmark II Folding 27.5" x 2.25" Rear
Shift Levers	SRAM X-5, 10 Speed
Front Derailleur	SRAM GX, 10 Speed
Rear Derailleur	SRAM GX, Medium Cage, Type 2, 10 Speed
Cassette	SRAM PG-1020 11-36, 10 Speed
Chain	SRAM PC-1031, 10 Speed
Crankset	SRAM FC800, 22/36 compact double with Power Spline, 10 Speed
Bottom Bracket	SRAM Power Spline, 73mm
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 Bolt Clamp, Adjuster
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Riser Bar 15mm rise, 31.8mm, 720mm Wide
Stem	Whyte Custom, 45mm S, M, 60mm L & XL
Grips	Whyte Custom Lock-on
Front Brakes	SRAM Level, 160mm Rotor
Rear Brakes	SRAM Level, 160mm Rotor, Internal Routing
Brake Levers	SRAM Level
Pedals	Fibre Reinforced Composite Platform

The 800 Series frame is brand new for 2017, using the very latest Whyte geometry based around a longer top tube, a short stem and wide 720mm bar. The 800 series bikes are also built around a 120mm travel fork, which brings trail bike levels of performance.

The BBX internal cable routing keeps cables clean and clear of grime whatever the conditions, while Whyte's surefooted geometry will make you want to ride come rain or shine.

WTB TCS i23 Asym rims with Maxxis TR front and rear specific tyres combine to make a Tubeless Ready package, with enough grip to fully exploit the 800 series trail geometry.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	12.9Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.5	74	604	303.5	789
M	66.5	74	623	303.5	807
L	66.5	74	641	303.5	832
XL	66.5	74	660	303.5	861

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1148	435	30.9	115	406
M	1168	435	30.9	125	444
L	1189	435	30.9	135	482.6
XL	1208	435	30.9	145	533

806 COMPACT-FIT

Trail Hardtail - 800 Series - 120mm

SRP £1,075



Colour	Matt Granite with Grey/Blue
Sizes Available	XS,S,M
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Tapered Headtube, Internal Cable Routing with BBX, Chainstay Post Mount Dropouts and Get A Grip seat clamp system
Fork	RockShox Recon Silver RL, 120mm Travel, Turn Key Lockout with Adjustable Rebound, Tapered Alloy Steerer with 100mm X 15mm Maxle
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, Sealed Cartridge Bearing 1.5" Lower, 1 1.8" Caged Upper Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 15mm X 100mm Through Axle, 32 Hole
Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
Rims	WTB Asym i23 Rims with TCS System, Tubeless Ready, 32 Hole
Tyres	Maxxis Ardent Folding 27.5" x 2.25" Front, Maxxis Crossmark II Folding 27.5" x 2.25" Rear
Shift Levers	Shimano SLX M7000, 11 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano SLX RD-M7000 Shadow Plus
Cassette	Shimano CS-M7000, 11-42, 11 Speed
Chain	Shimano HG-601, 11 Speed
Crankset	FSA Comet, Mega EXO, direct mount 32T, 11 Speed
Bottom Bracket	FSA Mega EXO, BSA, 73mm
Seatpost	Whyte 20mm Offset, 30.9mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom fit
Bar	Whyte Riser Bar 15mm rise, 31.8mm, 720mm Wide
Stem	Whyte Custom, 45mm
Grips	Whyte Custom Lock-on
Front Brakes	Tektro Auriga, 160mm rotor
Rear Brakes	Tektro Auriga, 160mm rotor, Internal Routing
Brake Levers	Tektro Auriga
Pedals	Fibre Reinforced Composite Platform

The 806 is available in the XS size, and all sizes sport more compact geometry than the 801 or 805. That means slightly less length for more comfortable reach suiting riders with shorter proportions.

The 806 uses the brand new SLX M7000 Shimano groupset. This 1 by 11 set up uses the latest Shadow Plus clutch rear derailleur combined with an FSA Comet narrow-wide chain ring for perfect chain control.

WTB TCS i23 Asym rims with Maxxis TR front and rear specific tyres combine to make a puncture-resistant, Tubeless Ready package, with enough grip to fully exploit the 800 series trail geometry.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	12.5Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	66.5	74	580	303.5	786
S	66.5	74	599	303.5	794
M	66.5	74	618	303.5	814
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1123	435	30.9	107	381
S	1143	435	30.9	115	406
M	1163	435	30.9	125	444

603 ZINC OPTION

Sports Hardtail - 600 Series - 100mm

SRP £570



Colour	Matt Zinc with Black/Lime
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Get A Grip seat clamp system, Internal Cable routing with BBX, Post Mount Chainstay Dropouts
Fork	SR XCM, 100mm Travel, Fixed Rebound Damping, Hydro Lockout
Rear Shock	N/A
Headset	FSA No.10, Semi integrated, Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	WTB SX19, 32 Hole
Tyres	WTB BeeLine Wire 27.5" x 2.2"
Shift Levers	Shimano Altus SL-M370-L, 9 Speed
Front Derailleur	Shimano Altus FD-M371, 9 Speed
Rear Derailleur	Shimano Acera RD-M3000-SGS, 9 Speed
Cassette	Shimano HG-200, 11-32, 9 Speed
Chain	KMC, 9 Speed
Crankset	Shimano FC-M371, 44-32-22, 9 Speed
Bottom Bracket	Square Taper, 73mm
Seatpost	Whyte 20mm Offset, 30.9mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte Riser Bar 30mm rise, 31.8mm, 700mm Wide
Stem	Whyte Custom, S, 45mm M,L,XL, 60mm
Grips	Whyte Custom, Composite Lock-on
Front Brakes	Tektro Auriga, HD-M290, 160mm Rotor
Rear Brakes	Tektro Auriga, HD-M290, 160mm Rotor, Internal Routing
Brake Levers	Tektro Auriga, HD-M290
Pedals	Fibre Reinforced Composite Platform

Our entry point bike punches well above its weight on the trails. The 600 Series frame is brand new for 2017, using the very latest Whyte geometry based around a longer top tube, a short stem and wide 700mm bar.

You'll find it hard to believe the 603 is Whyte's entry level mountain bike: with carefully chosen, branded parts and a well designed frame it has all the hallmarks of Whyte's award winning DNA.

This new frame bristles with UK design features such as the "Get A Grip" seat post clamp system. This allows quick adjustment, fantastic weather proofing and a nice ergonomic lever which is easy to operate however cold your hands might be.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	13.6Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5	74	604.8	303.5	778.5
M	68.5	74	623.8	303.5	796.5
L	68.5	74	642.8	303.5	821.5
XL	68.5	74	661.8	303.5	850.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1124	435	30.9	115	406
M	1144	435	30.9	125	444
L	1164	435	30.9	135	482.6
XL	1184	435	30.9	145	533

603 LIME

Sports Hardtail - 600 Series - 100mm

SRP £570



Colour	Matt Lime with Black/Blue
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Get A Grip seat clamp system, Internal Cable routing with BBX, Post Mount Chainstay Dropouts
Fork	SR XCM, 100mm Travel, Fixed Rebound Damping, Hydro Lockout
Rear Shock	N/A
Headset	FSA No.10, Semi integrated, Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	WTB SX19, 32 Hole
Tyres	WTB BeeLine Wire 27.5" x 2.2"
Shift Levers	Shimano Altus SL-M370-L, 9 Speed
Front Derailleur	Shimano Altus FD-M371, 9 Speed
Rear Derailleur	Shimano Acera RD-M3000-SGS, 9 Speed
Cassette	Shimano HG-200, 11-32, 9 Speed
Chain	KMC, 9 Speed
Crankset	Shimano FC-M371, 44-32-22, 9 Speed
Bottom Bracket	Square Taper, 73mm
Seatpost	Whyte 20mm Offset, 30.9mm 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte Riser Bar 30mm rise, 31.8mm, 700mm Wide
Stem	Whyte Custom, S, 45mm M,L,XL, 60mm
Grips	Whyte Custom, Composite lock-on
Front Brakes	Tektro Auriga, HD-M290, 160mm Rotor
Rear Brakes	Tektro Auriga, HD-M290, 160mm Rotor, Internal Routing
Brake Levers	Tektro Auriga, HD-M290
Pedals	Fibre Reinforced Composite Platform

Our entry point bike punches well above its weight on the trails. The 600 Series frame is brand new for 2017, using the very latest Whyte geometry based around a longer top tube, a short stem and wide 700mm bar.

You'll find it hard to believe the 603 is Whyte's entry level mountain bike: with carefully chosen, branded parts and a well designed frame it has all the hallmarks of Whyte's award winning DNA.

This new frame bristles with UK design features such as the "Get A Grip" seat post clamp system. This allows quick adjustment, fantastic weather proofing and a nice ergonomic lever which is easy to operate however cold your hands might be.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	13.6Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5	74	604.8	303.5	778.5
M	68.5	74	623.8	303.5	796.5
L	68.5	74	642.8	303.5	821.5
XL	68.5	74	661.8	303.5	850.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1124	435	30.9	115	406
M	1144	435	30.9	125	444
L	1164	435	30.9	135	482.6
XL	1184	435	30.9	145	533

604 COMPACT-FIT

Sports Hardtail - 600 Series - 100mm

SRP £570



Colour	Matt Aqua with Black/Orange
Sizes Available	XS,S,M,L
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Get A Grip seat clamp system, Internal Cable routing with BBX, Post Mount Chainstay Dropouts
Fork	SR XCM, 100mm Travel, Fixed Rebound Damping, Hydro Lockout
Rear Shock	N/A
Headset	FSA No.10, Semi integrated, Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	WTB SX19, 32 Hole
Tyres	WTB BeeLine Wire 27.5" x 2.2"
Shift Levers	Shimano Altus SL-M370-L, 9 Speed
Front Derailleur	Shimano Altus FD-M371, 9 Speed
Rear Derailleur	Shimano Acera RD-M3000-SGS, 9 Speed
Cassette	Shimano HG-200, 11-32, 9 Speed
Chain	KMC, 9 Speed
Crankset	Shimano FC-M371, 44-32-22, 9 Speed
Bottom Bracket	Square Taper, 73mm
Seatpost	Whyte 20mm Offset, 30.9mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte Riser Bar 30mm rise, 31.8mm, 700mm Wide
Stem	Whyte Custom, XS,S, 45mm M,L, 60mm
Grips	Whyte Custom, Composite Lock-on
Front Brakes	Tektro Auriga, HD-M290, 160mm Rotor
Rear Brakes	Tektro Auriga, HD-M290, 160mm Rotor, Internal Routing
Brake Levers	Tektro Auriga, HD-M290
Pedals	Fibre Reinforced Composite Platform

Our Compact MTBs feature shorter geometry and components to better fit a smaller rider. The 604 may be our entry level model, but with carefully chosen parts and an exceptional frame it remains distinctly Whyte.

The 600 Series frame is brand new for 2017, using the very latest Whyte geometry, lightweight multi-butt construction, and tidy BBX internal cable routing.

This new frame bristles with UK design features such as the "Get A Grip" seat post clamp system. This allows quick adjustment, fantastic weather proofing and a nice ergonomic lever which is easy to operate however cold your hands might be.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	13.7Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	68.5	74	581	303.5	764
S	68.5	74	600	303.5	783.5
M	68.5	74	619	303.5	803.5
L	68.5	74	638	303.5	829
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1100	435	30.9	107	381
S	1120	435	30.9	115	406
M	1140	435	30.9	125	444
L	1160	435	30.9	135	482.6

605

Sports Hardtail - 600 Series - 100mm

SRP £670



Colour	Mat: Orange with Denim/Grey
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Get A Grip seat clamp system, Internal Cable routing with BBX, Post Mount Chainstay Dropouts
Fork	Rockshox XC-30, 100mm Travel, Alloy Steerer, Adjustable Rebound, Turnkey Lockout
Rear Shock	N/A
Headset	FSA No.10, Semi integrated, Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	WTB SX-19, 32 Hole
Tyres	WTB BeeLine Wire 27.5" x 2.2"
Shift Levers	Shimano Acera M3000, 9 Speed
Front Derailleur	Shimano Acrea M-3000, 9 Speed
Rear Derailleur	Shimano Alivio RD-M4000 Shadow, 9 Speed
Cassette	Shimano HG-200-9, 11-34, 9 Speed
Chain	KMC HG-53, 9 Speed
Crankset	Shimano M3000, 40-30-22, 9 Speed
Bottom Bracket	Shimano BB-UN26 Square Taper, 73mm
Seatpost	Whyte 20mm Offset, 30.9mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte Riser Bar 30mm rise DB, 31.8mm, 700mm Wide
Stem	Whyte Custom, S, 45mm, M, L, XL 60mm
Grips	Whyte Custom Composite Lock-on
Front Brakes	Tektro Auriga, HD-M290, 160mm Rotor
Rear Brakes	Tektro Auriga, HD-M290, 160mm Rotor, Internal Routing
Brake Levers	Tektro Auriga, HD-M290
Pedals	Fibre Reinforced Composite Platform

The 600 Series frame is brand new for 2017, using the very latest Whyte geometry based around a longer top tube, a short stem and wide 700mm bar. This gives this entry-point bike exceptional performance on the trails.

This new frame bristles with UK design features such as the "Get A Grip" seat post clamp system. This allows quick adjustment, fantastic weather proofing and a nice ergonomic lever which is easy to operate however cold your hands might be.

For 2017 the 605 features a Rockshox XC-30 front fork. This boost in performance helps the rider get the most out of the all new 600 Series geometry.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	13.2Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5	74	604.8	303.5	778.5
M	68.5	74	623.8	303.5	796.5
L	68.5	74	642.8	303.5	821.5
XL	68.5	74	661.8	303.5	850.5

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1124	435	30.9	115	406
M	1144	435	30.9	125	444
L	1164	435	30.9	135	482.6
XL	1184	435	30.9	145	533

T-129S

T-129 Trail 29er Suspension - 120mm

SRP £2,450



Colour	Matt Lime with Grey/Denim
Sizes Available	M,L,XL
Frame	6061 T6 SCR Aluminium Front Triangle with Tapered Head Tube and Intergrip integrated seat clamp system, alloy symmetrical SCS rear Triangle, Boost 148mm Dropouts, Shimano Direct Mount hanger
Fork	Fox Float Rhythm 34, 29", 120mm Travel with Sweep-Adj, Grip Damper, Tapered steerer and 110mm x 15mm Boost E-Thru Axle
Rear Shock	Fox Float DPS Performance, Rebound Adjustment and 3pos, Evol LV
Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Upper Bearing
Rear Hub	Alloy, Double Sealed Cartridge Bearing, 12mm X 148mm Boost Through Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing, 15mm X 110mm Boost Through Axle, 32 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless Steel Spokes, Brass Nipples
Rims	RaceFace AR-27, 27mm wide 29" Rims with Tubeless Ready, 32 Hole
Tyres	Maxxis Tomahawk TR, 3C Maxx Terra, 29" X 2.3", Folding, Front, Maxxis, Crossmark II, DU EXO, 29" X 2.25, Folding, Rear
Shift Levers	Shimano SLX M7000, I-spec, 11 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano SLX M7000, 11 Speed, Shadow Plus, Direct Mount
Cassette	Shimano SLX M7000, 11-42, 11 Speed
Chain	Shimano HG601-11, 11 Speed
Crankset	RaceFace Affect, direct mount 28T chainring, 11 Speed
Bottom Bracket	RaceFace BSA, 73mm
Seatpost	RockShox Reverb Stealth 150/150/170mm, 30.9mm
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Custom Alloy, 15mm Rise, 760mm Wide M/L 30mm Rise, 780mm Wide XL
Stem	Whyte Gravity Stem, 40mm M/L, 50mm XL
Grips	Whyte Lock-on
Front Brakes	Shimano BR-M615 I-spec, 180mm Rotor
Rear Brakes	Shimano BR-M615 I-spec, 160mm Rotor, Internal Routing
Brake Levers	Shimano BR-M615 I-spec
Pedals	None

The entry point to the T-129 range features a Rockshox Reverb Stealth seatpost and Whyte's integrated "Intergrip" seat post system. This neat solution gives the T-129S a clean look and fantastic weather-proofing.

The Geometry of the T-129S is the same as the 5/5 award winning T-129 RS from 2016. These angles are the very latest in progressive trail geometry from Whyte.

Shimano's new SLX uses cascade technology from the XT 1 by 11 groupset to bring a truly affordable performance drive train. Whyte has combined this with a 30mm alloy axled Race Face crank that fits into a BSA BB for a light, stiff and durable combination.

Dropout Code	DROPWHQ4SD2
Shock Stroke and Sag Setting	63mm, Sag 19mm (30%)
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	216mm
Weight	14.1Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	67.0 +0/-1	74.2	583.4	335	800
M	67.0 +0/-1	74	613.4	335	805
L	67.0 +0/-1	73.8	633.1	335	810
XL	67.0 +0/-1	73.6	652.8	335	815
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1156.1	430.9	30.9	100	406.4
M	1176.1	430.9	30.9	100	431.8
L	1196.1	430.9	30.9	110	457.2
XL	1216.1	430.9	30.9	120	482.6

T-129 RS

T-129 Trail 29er Suspension - 120mm

SRP £2,950



Colour	Matt Zinc with Grey/Orange
Sizes Available	M,L,XL
Frame	6061 T6 SCR Aluminium Front Triangle with Tapered Head Tube and Intergrip integrated seat clamp system, alloy symmetrical SCS rear Triangle, Boost 148mm Dropouts, Shimano Direct Mount hanger
Fork	Fox Float Performance 34, 29", 120mm Travel with 3Pos Grip Damper, Tapered steerer and 110mm x 15mm Boost E-Thru Axle
Rear Shock	Fox Float DPS Performance, Rebound Adjustment and 3pos Adjust Evol LV
Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Upper Bearing
Rear Hub	Hope PR04 with StSt Bearings, 12mm X 148 mm Boost Through Axle, 11 Speed Shimano Freehub, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing, 15mm X 110mm Boost Through Axle, 32 Hole
Spokes	DT Swiss Champion 2.0mm with Brass Nipples
Rims	RaceFace ARC-27, 27mm wide Welded 29" Rims with Tubeless Ready, 32 Hole
Tyres	Maxxis Tomahawk TR, 3C Maxx Terra, 29" X 2.3", Folding, Front, Maxxis, Crossmark II, DU EXD, 29" X 2.25, Folding Rear
Shift Levers	Shimano XT M8000, I-spec II, 11 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano XT M8000, 11 Speed, Shadow Plus, Direct Mount
Cassette	Shimano XT M8000, 11-46, 11 Speed
Chain	Shimano XT HG-601, 11 Speed
Crankset	RaceFace Turbine Clinch, direct mount chainring 30T, 11 Speed, Alloy with 30mm alloy axle
Bottom Bracket	RaceFace BSA, 73mm
Seatpost	RockShox Reverb Stealth 150/150/170mm, 30.9mm
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Custom Alloy, 15mm Rise, 760mm Wide M/L 30mm Rise, 780mm Wide XL
Stem	Whyte Gravity Stem, 40mm M/L, 50mm XL
Grips	Whyte Lock-on
Front Brakes	Shimano XT M8000, 180mm Rotor
Rear Brakes	Shimano XT M8000, 160mm Rotor, Internal Routing
Brake Levers	Shimano XT M8000, I-spec II
Pedals	

Like all our suspension bikes, the RS features our single ring specific SCR frame with mega stiff symmetrical chainstays, a full width main pivot for extended bearing life and maximised suspension performance.

The T-129 RS won 5/5 in MBUK in 2016, and for 2017 we have further improved the bike with increased tyre clearance, wider rims and tyres.

The T-129 RS features a wish-list parts pick from Fox, Shimano, RaceFace and Hope.

Dropout Code	DROPWHQ4SD2
Shock Stroke and Sag Setting	63mm, Sag 19mm (30%)
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	216mm
Weight	13.8Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	67.0 +0/-1	74	613.4	335	805
L	67.0 +0/-1	73.8	633.1	335	810
XL	67.0 +0/-1	73.6	652.8	335	815

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1176.1	430.9	30.9	100	431.8
L	1196.1	430.9	30.9	110	457.2
XL	1216.1	430.9	30.9	120	482.6

529

Trail Hardtail 29er - 120mm

SRP £875



Colour	Matt Lime with Black/Denim
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Tapered Headtube, Internal Cable Routing with BBX, Chainstay Post Mount Dropouts and Get A Grip seat clamp system
Fork	SR Suntour Raidon, 120mm Travel, Alloy Tapered Steerer, Adjustable Rebound and Lockout, 100mm X 15mm through axle
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, Sealed Cartridge Bearing 1.5" Lower, 1 1.8" Caged Upper Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 15mm X 100mm Through Axle, 32 Hole
Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
Rims	Whyte Trail-21, sleeve joint, Offset rims, 29", 32 Hole
Tyres	Maxxis Ardent 60TPI, 29"x 2.25", Front, Maxxis Crossmark II 60TPI, 29" x 2.25", Rear.
Shift Levers	Shimano Acera M3000, 9 Speed
Front Derailleur	Shimano Deore M618, 10 Speed
Rear Derailleur	Shimano Deore RD-M592 Shadow
Cassette	Shimano HG-200, 11-34, 9 Speed
Chain	Shimano HG-53, 9 Speed
Crankset	SR Suntour XCM, Compact Double 36-22, 9 Speed, 2pcs
Bottom Bracket	SR Suntour, 73mm
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Flat 29er 6061 Bar, 31.8mm, 720mm Wide
Stem	Whyte Custom, -6 Degree, 45mm S and M and 60mm Large and XL
Grips	Whyte Custom Lock-on
Front Brakes	Tektro Auriga, 160mm rotor
Rear Brakes	Tektro Auriga, 160mm rotor, Internal Routing
Brake Levers	Tektro Auriga
Pedals	Fibre Reinforced Composite Platform

Our Alloy 29er hardtail frame is brand new for 2017, using the very latest Whyte geometry based around a longer top tube, a short stem and wide 720mm bar. The 2017 bikes are also built around a 120mm travel fork, which brings trail bike levels of performance.

A 15mm through-axle fork, 21mm wide trail rims and front and rear specific tyres give the 529 true trail bike performance at an affordable price point.

This new frame bristles with UK design features such as the "Get A Grip" seat post clamp system. This allows quick adjustment, fantastic weather proofing and a nice ergonomic lever which is easy to operate however cold your hands might be.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	13.4Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.5	74	614	305	810
M	66.5	74	633	305	820
L	66.5	74	653	305	846
XL	66.5	74	671	305	860

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1163	440	30.9	110	406.4
M	1183	440	30.9	115	444.5
L	1203	440	30.9	120	495.7
XL	1223	440	30.9	135	533.4

629

Trail Hardtail 29er - 120mm

SRP £1,050



Colour	Matt Zinc with Orange/Black
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Tapered Headtube, Internal Cable Routing with BBX, Chainstay Post Mount Dropouts and Get A Grip seat clamp system
Fork	RockShox Recon Silver RL 29", Solo Air, 120mm Travel, Alloy Tapered Steerer, Lock out and rebound, 100 X 15mm Maxle
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, Sealed Cartridge Bearing 1.5" Lower, 1 1.8" Caged Upper Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 15 X 100mm Through axle, 32 Hole
Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
Rims	WTB Asym i23 29" Rims with TCS System, Tubeless Ready, 32 Hole
Tyres	Maxxis Ardent TR 60TPI, 29"x 2.25", Folding, Front, Maxxis Crossmark II TR 60TPI, 29" x 2.25", Folding, Rear.
Shift Levers	SRAM NX, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM NX, 11 Speed
Cassette	SRAM PG-1030, 11-42, 11 Speed
Chain	SRAM PC-1110, 11 Speed
Crankset	SRAM NX, XSYNC 32T, 11 Speed
Bottom Bracket	SRAM GXP, 73mm
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Flat 29er 6061 Bar, 31.8mm, 720mm Wide
Stem	Whyte Custom, -6 Degree, 45mm S and M and 60mm Large and XL
Grips	Whyte Custom Lock-on
Front Brakes	SRAM Level, 180mm Rotor
Rear Brakes	SRAM Level, 160mm Rotor, Internal Routing
Brake Levers	SRAM Level
Pedals	Fibre Reinforced Composite Platform

Our Alloy 29er hardtail frame is brand new for 2017, using the very latest Whyte geometry based around a longer top tube a short stem and wide 720mm bar. The 2017 bikes are also built around a 120mm travel fork, which brings trail bike levels of performance.

This new frame bristles with UK design features such as the "Get A Grip" seat post clamp system. This allows quick adjustment, fantastic weather proofing and a nice ergonomic lever which is easy to operate however cold your hands might be.

The 629 gets a full trail bike upgrade for 2017 with a 1 by 11 SRAM NX drivetrain, 120mm Recon Silver fork and 23mm wide WTB TCS tyres with Maxxis TR tyres.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	12.5Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.5	74	614	305	810
M	66.5	74	633	305	820
L	66.5	74	653	305	846
XL	66.5	74	671	305	860

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1163	440	30.9	110	406.4
M	1183	440	30.9	115	444.5
L	1203	440	30.9	120	495.7
XL	1223	440	30.9	135	533.4

29-CS

Carbon Performance Hardtail 29er - C29 Series

SRP £2,299



Colour	Matt Black with Lime / Grey
Sizes Available	S,M,L
Frame	Uni-directional Multi Monocoque with DOX internal cable routing, Post Mount chainstay mounted disc brake and full carbon dropouts, Inter-Grip integrated seat clamp system
Fork	RockShox Reba RL 29", 100mm Travel, Tapered steerer, Remote lock-out and 100mm x 15mm Maxle
Rear Shock	N/A
Headset	FSA No. 42 Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, Shimano XT QR, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 15mm X 100mm Through Axle, 32 Hole
Spokes	Black Stainless Steel
Rims	RaceFace AR-27, 27mm wide Tubeless ready Rims, Tubeless Ready
Tyres	Maxxis IKON TR, 29" X 2.2" 120TPI, 3C(Maxx Terra) Folding Bead, EXO Sidewall protection
Shift Levers	Shimano XT I Spec II, 11 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano XT M8000, Shadow Plus, 11 Speed
Cassette	Shimano XT M8000, 11-42, 11 Speed
Chain	Shimano, HG600, 11 Speed
Crankset	FSA Comet, Mega EXO, direct mount 32T, 11 Speed
Bottom Bracket	FSA Mega EXO, BSA, 73mm
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 Bolt Clamp, Adjuster
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Flat 29er 6061 Bar, 31.8mm, 720mm Wide
Stem	Whyte Custom, -6 Degree, 70mm S, 80mm M & L
Grips	Whyte Lock-on, EVA Light-weight Foam
Front Brakes	Shimano XT, 180mm Rotor
Rear Brakes	Shimano XT, 160mm Rotor, Internal Routing
Brake Levers	Shimano XT I Spec II
Pedals	N/A

The 29CS wheelset comes with RaceFace AR-27 rims laced to Whyte's double sealed cartridge bearing hubs with DT Swiss spokes making for a light-weight and durable wheelset.

This bike will not only get you round your favourite XC loop in record time, it will also give you the control and balance of the very best of our Whyte trail bikes.

Using our undersize/oversize chassis design for outstanding power transfer and pin sharp tracking, combined with fatigue reducing compliance, this is a high-speed bike you can ride all day.

Dropout Code	DROPWH20
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	10.9Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.3	72.8	612.2	304	789
M	69.3	72.8	627	304	809
L	69.3	72.8	640.8	304	844
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1117.3	437.5	30.9	100	406
M	1127.9	437.5	30.9	110	444.5
L	1144.9	437.5	30.9	120	495.7

29-C TEAM

Carbon Performance Hardtail 29er - C29 Series

SRP £3,999



Colour	Matt Black with Orange/Grey
Sizes Available	S, M, L
Frame	Uni-directional Multi Monocoque with DOX internal cable routing, Post Mount chainstay mounted disc brake and full carbon dropouts, Inter-Grip integrated seat clamp system
Fork	Fox Float SC 32, 29", 100mm Travel with 3Pos-Adj FIT4 Damper, Kashima coating, Tapered steerer and 110mm x 15mm Boost E-Thru Axle
Rear Shock	N/A
Headset	FSA No. 42 Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings
Rear Hub	Whyte XC-209-Carbon Team Wheelset, 32 StSt spokes, Whyte Cartridge bearing, XD Driver, Micro engagement freehub, 32 Hole
Front Hub	Whyte XC-209-Carbon Team Wheelset, 28 StSt spokes, Whyte Boost 15mm x 110mm Through Axle, 28 Hole
Spokes	Double Butted Black Stainless Steel
Rims	Whyte X-C-209-Carbon Team Uni-Directional High-Modulus Carbon, 23mm wide, Tubeless Ready
Tyres	Maxxis IKON TR, 29" X 2.2" 120TPI, 3C(Maxx Terra) Folding Bead, EXO Sidewall protection
Shift Levers	SRAM XX1 Eagle, MMX Matchmaker, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM XX1 Eagle, 12 Speed
Cassette	SRAM XG Eagle XG-1295 10-50, 12 Speed
Chain	SRAM PCXX1 Eagle, 12 Speed
Crankset	SRAM XX1 Eagle, XSYNC 2 direct mount 34T chainring, 12 Speed
Bottom Bracket	SRAM GXP Team, 73mm
Seatpost	RaceFace NEXT, Matt UD Carbon, 30.9mm x 400mm, 2 bolt clamp
Seat	Prologo Custom X-Zero, Ti Rail
Bar	RaceFace NEXT, Matt UD Carbon, Flat Bar, 31.8mm, 720mm Wide
Stem	Whyte Custom, -6 Degree, 70mm S, 80mm M & L
Grips	Whyte Lock-on, EVA Light-weight Foam
Front Brakes	SRAM Level Ultimate, 180mm CLX 2-piece Rotor, StSt hardware
Rear Brakes	SRAM Level Ultimate, 160mm CLX 2-piece Rotor, StSt hardware, Internal Routing
Brake Levers	SRAM Level Ultimate, MMX Matchmaker
Pedals	N/A

With the best of everything, including the all-new, Fox SC 32 fork with Boost and Kashima coating, Whyte in-house Carbon wheels and Raceface NEXT finishing kit, this is a ready "out of the box" race bike.

The 29-C Team comes with the all new SRAM XX1 Eagle 1 by 12 drive train. This massive spread of rear sprockets gives the range to increase the front chainring to a 34T, giving even more speed at the top end with no compromise on your climbing gear.

Using our undersize/oversize chassis design for outstanding power transfer and pin sharp tracking, combined with fatigue reducing compliance, this is a high-speed bike you can ride all day.

Dropout Code	DROPWH20
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	9.6Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.3	72.8	612.2	304	789
M	69.3	72.8	627	304	809
L	69.3	72.8	640.8	304	844

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1117.3	437.5	30.9	100	406
M	1127.9	437.5	30.9	110	444.5
L	1144.9	437.5	30.9	120	495.7

FRISTON

Gravel/Adventure - GX Series

SRP £1,499



Colour	Matt Orange with Black/Denim
Sizes Available	52,54,56,58
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted, Chainstay Flat Mount 160 Disc mount, DOX cable routing with Inter-Grip integrated seat clamp system
Fork	Straight Bladed Carbon Front Fork with Internal Hose Routing, tapered alloy steerer, Flat Mount dropouts and 15mm Through Axle
Rear Shock	N/A
Headset	FSA No. 42 Integrated Road, 1 1/8" upper Sealed Cartridge Bearing, 1.5 lower Sealed Cartridge Bearing
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 12mm X 142mm Through Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 15mm X 100mm Through Axle, 32 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless with Brass Nipples
Rims	WTB Asym i23 TCS, Tubeless Ready, 32 Hole
Tyres	WTB Rambler, TCS, DNA Compound, Folding, 700 x 40c
Shift Levers	SRAM Rival 1, Full Hydraulic, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM Rival 1, Long Cage, 11 Speed
Cassette	SRAM PC-1130 11-42, 11 Speed
Chain	SRAM PC-1110, 11 Speed
Crankset	SRAM S350, XSYNC 3BT chainring, 175mm Crank Length
Bottom Bracket	SRAM GXP, 68mm
Seatpost	Whyte 20mm Offset, 30.9mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Light Weight Triple Density Base, Triple Panel Design
Bar	Whyte Gravel, 480mm Wide
Stem	Whyte -6 Deg, 70mm 52mm, 80mm 54, 90mm 56mm & 58mm
Grips	Whyte Anti Slip, Cross Bar Tapes
Front Brakes	SRAM Rival 1 Hydraulic, 160mm Rotor
Rear Brakes	SRAM Rival 1 Hydraulic, 160mm Rotor
Brake Levers	SRAM Rival 1 Hydraulic
Pedals	None

The Friston takes everything we've learnt from MTBs and puts that knowledge into a great value Gravel/Adventure bike package. With hydraulic discs, ground-breaking geometry and SRAM's innovative Rival 1 groupset, this bike is ready for anything from a CX Race to an all-day adventure.

We have applied our unique Whyte frame geometry to the Friston, creating Whyte's most versatile all-terrain bike. It's equally at home riding your favourite bridle path, winter training or even commuting. Alternatively, try a CX race this winter or a long haul off road adventure - this bike can do it all!

A straight bladed carbon fork with a tapered steerer tube, internal hose routing and 15mm through axle, give this bike great front end stiffness and steering precision.

Dropout Code	DROPWH17
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	10.Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
52	70	74	566	277	787
54	70	74	585	277	802
56	70	74	604	277	817
58	70	74	623	277	832

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
52	1036	415	30.9	145	520
54	1056	415	30.9	160	540
56	1076	415	30.9	175	560
58	1096	415	30.9	190	580

GISBURN

Gravel/Adventure - GX Series

SRP £1,899



Colour	Matt Lime with Black/Denim
Sizes Available	52,54,56,58
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted, Chainstay Flat Mount 160 Disc mount, DOX cable routing with Inter-Grip integrated seat clamp system
Fork	Straight Bladed Carbon Front Fork with Internal Hose Routing, tapered alloy steerer, Flat Mount dropouts and 15mm Through Axle
Rear Shock	N/A
Headset	FSA No. 42 Integrated Road, 1 1/8" upper Sealed Cartridge Bearing, 1.5 lower Sealed Cartridge Bearing
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, XD Driver, 12mm X 142mm Through Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 15mm X 100mm Through Axle, 32 Hole
Spokes	DT Champion 2.0mm with Brass Nipples
Rims	WTB Asym i23, 23mm TCS Rims
Tyres	WTB Riddler, Fast Light Rolling TCS, DNA Compound, Folding, 700 x 37c
Shift Levers	SRAM Force 1, 11 Speed Carbon Hydraulic Levers
Front Derailleur	N/A
Rear Derailleur	SRAM Force 1, Mid Cage, 11 Speed
Cassette	SRAM PG-1175, 11-42, 11 Speed
Chain	SRAM PCX1110
Crankset	SRAM Force 1, XSYNC 38T chainring, 175mm Crank Length, Carbon
Bottom Bracket	SRAM GXP Team, 68mm
Seatpost	KS Speed Up, 100mm dropper post with nose lever control
Seat	Whyte Custom, Light Weight Triple Density Base, Triple Panel Design
Bar	Whyte Gravel, 480mm Wide
Stem	Whyte -6 Deg, 70mm 52mm, 80mm 54, 90mm 56mm & 58mm
Grips	Whyte Anti Slip, Cross Bar Tapes
Front Brakes	SRAM Force 1, 160mm Rotor
Rear Brakes	SRAM Force 1, 160mm Rotor, Internal Routing
Brake Levers	SRAM Force 1, Carbon
Pedals	None

A truly ground-breaking Gravel/Adventure bike with MTB-inspired geometry, tubeless ready wheels and tyres, hydraulic disc brakes and SRAM's innovative Force 1 groupset and a dropper post so you can make the most out of the geometry on the descents.

Whyte geometry makes this bike exceptionally competent and controllable off-road. "1 by 11" technology offers simplicity and efficiency that cannot be rivalled. Full hydraulic disc brakes add stopping power and control.

Whyte's straight bladed carbon fork with its tapered steerer tube and 15mm through axle gives this bike great front end stiffness and steering precision. Combined with an ultra-wide 480mm wide bar which allows the rider to truly exploit the radical geometry.

Dropout Code	DROPWH17
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	9.9Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
52	70	74	566	277	787
54	70	74	585	277	802
56	70	74	604	277	817
58	70	74	623	277	832

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
52	1036	415	30.9	145	520
54	1056	415	30.9	160	540
56	1076	415	30.9	175	560
58	1096	415	30.9	190	580

WESSEX

Performance Road Disc - RDC7 Series

SRP £2,150



Colour	Matt Zinc with Lime/Grey
Sizes Available	52,54,56,58
Frame	Uni-directional Multi Monocoque with Flat Mount 160 Disc mount, DOX internal cable routing, Verti-Grip integrated seat clamp system, concealed eyelets for Mud Guards and 142mm rear dropouts with 12mm through axle
Fork	Straight Bladed Carbon Front Fork, Tapered Alloy Steerer with, 12mm x 100mm through axle, concealed eyelets for Mud Guards
Rear Shock	N/A
Headset	FSA No. 42 Integrated Road, 1 1/2" lower and 1 1/8" upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, Centre-lock, 12mm x 142mm Through Axle, 28 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, Centre-lock, 12mm x 100mm Through Axle, 28 Hole
Spokes	DT Competition butted, Black Sandvik Stainless with Black Brass Nipples
Rims	Easton AR-21, 21mm wide Tubeless Ready Rims, 28 Hole
Tyres	Schwalbe S-ONE, 700 x 32c, TL-Easy Tubeless System, MicroSkin Puncture Protection, Folding
Shift Levers	Shimano ST-685 Ultegra, 11 Speed
Front Derailleur	Shimano FD-5800 105, 11 Speed
Rear Derailleur	Shimano RD-6800 GS Ultegra, 11 Speed
Cassette	Shimano CS-5800 105 11-32, 11 Speed
Chain	Shimano, HG-601, 11 Speed
Crankset	FSA Gossamer Pro EVO-386 DB 34-50, 11 Speed, Compact Double
Bottom Bracket	FSA EVO-8681, 68mm
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 1pcs 3d Forged 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom Road, with lightweight foam, Triple Panel Design
Bar	Whyte Road, 31.8mm, Compact "Wing" Bar
Stem	Whyte -6 Deg/6 Deg, 100mm 52cm, 110mm 54cm, 120mm 56/58cm
Grips	Whyte Anti Slip with 3M Reflective logos on tapes
Front Brakes	Shimano BR-805 Hydraulic, Centre-lock 160mm Rotor, Internal Routing
Rear Brakes	Shimano BR-805 Hydraulic, Centre-lock 160mm Rotor, Internal Routing
Brake Levers	Shimano ST-685 Ultegra
Pedals	Fibre Reinforced Composite Platform

The all new Wessex is conceived to be the ideal British road bike. Developed and specified for riding on all road surfaces, the Wessex uses the very latest in tubeless ready, high air volume Schwalbe tyres on 21mm wide Easton AR rims.

Whether you're commuting longer distances, winter training or entering summer sportifs, the Whyte Road Disc range offers Cyclo Cross durability with pure Road geometry.

12mm through axles, tubeless tyres, disc brakes and the ability to fit full length mud guards makes the Wessex arguably the most versatile and capable carbon road bike we have ever made.

Dropout Code	DROPWH17
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	8.8Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
52	72.5	74	540	271.5	781.5
54	73	73.5	555	271.5	798.5
56	73	73	570	271.5	814.5
58	73	73	585	271.5	830.5

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
52	998.4	425	27.2	145	520
54	1003.3	425	27.2	160	540
56	1012.8	425	27.2	175	560
58	1027.8	425	27.2	190	580

SUSSEX

Sports Road/Commuter Disc - RD7 Series

SRP £850



Colour	Matt Zinc with Grey/Lime
Sizes Available	50,52,54,56,58
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Flat Mount 160 Chainstay Disc mount
Fork	Alloy fork, Alloy tapered steerer, Flat Mount disc brake mount, Internal Routing, Fender eyelets
Rear Shock	N/A
Headset	FSA No. 42 Integrated Road, 1 1/2" lower Sealed Cartridge Bearing and 1 1/8" upper Sealed Ball Retainer
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless with Black Brass Nipples
Rims	Whyte Disc Road 20mm Deep, 20mm Wide, Offset Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyres	Maxxis, Rouler 700 x 28c, 60tpi, wire bead , Maxxshield K2 + Silkworm
Shift Levers	Shimano ST-R3000 SORA, 9 Speed
Front Derailleur	Shimano FD-R3000 SORA, 9 Speed
Rear Derailleur	Shimano RD-R3000 SORA, 9 Speed
Cassette	Shimano HG-300, 11-34, 9 Speed
Chain	Shimano HG53, 9 Speed
Crankset	Shimano R345-L, 34-50, Octalink, 9 Speed, Compact Double
Bottom Bracket	Shimano BB-ES300, Octalink, 68mm
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 1pcs 3D Forged 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Road, 31.8mm, Compact "Wing" Bar
Stem	Whyte -6 Deg/6 Deg, 100mm 52cm, 110mm 54cm/56cm, 120mm 58cm
Grips	Whyte Anti Slip with 3M Reflective logos on tapes
Front Brakes	ProMax, Decode R Dual Pull Mechanicals, Flat Mount, Linear outer cables with Kevlar Reinforcement, 160mm Rotor, Internal Routing
Rear Brakes	ProMax, Decode R Dual Pull Mechanicals, Flat Mount, Linear outer cables with Kevlar Reinforcement, 160mm Rotor, Internal Routing
Brake Levers	Shimano ST-R3000 SORA
Pedals	Fibre Reinforced Composite Platform

Whether you're commuting longer distances, winter training or entering summer sports, the Whyte road disc range offers Cyclo Cross levels of durability with pure road speed.

Our lightweight aluminium frame offers large tyre clearances, great geometry and reliable disc braking, making it a perfect companion for big rides out in the hills.

A strong alloy 6061 frame, with mudguard and rack eyelets, combined with wide width, offset rimmed RD-7 wheels and disc brakes will give years of reliable all-season performance.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	10.3Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
50	72	74.5	525	271.5	763.5
52	72.5	74	540	271.5	781.5
54	73	73.5	555	271.5	798.5
56	73	73	570	271.5	814.5
58	73	73	585	271.5	830.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
50	992.9	425	27.2	130	500
52	998.4	425	27.2	145	520
54	1003.3	425	27.2	160	540
56	1012.8	425	27.2	175	560
58	1027.8	425	27.2	190	580

SOMERSET COMPACT-FIT

Sports Road/Commuter Disc - RD7 Series

SRP £850



Colour	Matt Aqua with Black/Grey
Sizes Available	47,49,51,53
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Flat Mount 160 Chainstay Disc mount
Fork	Alloy fork, Alloy tapered steerer, Flat Mount disc brake mount, Internal Routing, Fender eyelets
Rear Shock	N/A
Headset	FSA No. 23 Integrated Road, 1 1/2" lower Sealed Cartridge Bearing and 1 1/8" upper Caged Double Sealed
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless with Black Brass Nipples
Rims	Whyte Disc Road 20mm Deep x 20mm Wide, Offset Section Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyres	Maxxis, Rouler 700 x 28c, 60tpi, wire bead , Maxxshield K2 + Silkworm
Shift Levers	Shimano ST-R3000 SORA, 9 Speed
Front Derailleur	Shimano FD-R3000 SORA, 9 Speed
Rear Derailleur	Shimano RD-R3000 SORA, 9 Speed
Cassette	Shimano HG-300, 11-34, 9 Speed
Chain	Shimano HG53, 9 Speed
Crankset	FSA Vero Adventure Pro, Solid Forged, MegaExo, 165mm, 48-32
Bottom Bracket	Shimano BB-ES300, Octalink, 68mm
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 3D Forged 6061Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Road, 31.8mm, Compact "Wing" Bar
Stem	Whyte -6 Deg/6 Deg, 80mm 47cm/49cm, 90mm 51cm, 100mm 53cm
Grips	Whyte Anti Slip with 3M Reflective logos on tapes
Front Brakes	ProMax, Decode R Dual Pull Mechanicals, Flat Mount, Linear outer cables with Kevlar Reinforcement, 160mm Rotor, Internal Routing
Rear Brakes	ProMax, Decode R Dual Pull Mechanicals, Flat Mount, Linear outer cables with Kevlar Reinforcement, 160mm Rotor, Internal Routing
Brake Levers	Shimano ST-3000 SORA
Pedals	Fibre Reinforced Composite Platform

The Somerset's compact geometry makes for a more comfortable female-focused fit. Combined with lightweight aluminium tubing and an 18spd Shimano drivetrain you have a bike that loves the hills.

A strong alloy 6061 frame, with mudguard and rack eyelets, combined with wide section RD-7 rims and disc brakes that will give years of reliable all-season performance.

Ergonomic Wing handlebar, combined with tuned bar width and stem length make for a comfortable fit.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	10.2Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
47	71.5	75	507	269	721
49	72	74.5	515	271.5	742.5
51	72.5	74	525	271.5	776.5
53	73	73.5	535	271.5	793.5

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
47	984.8	425	27.2	115	470
49	985	425	27.2	130	490
51	985.4	425	27.2	145	510
53	985.4	425	27.2	160	530

DORSET

Sports Road/Commuter Disc - RD7 Series

SRP £1,060



Colour	Matt Granite with Blue/Grey
Sizes Available	52,54,56,58
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Flat Mount 160 Chainstay Disc mount
Fork	Straight Bladed Carbon Front Fork, Tapered Alloy Steerer with Internal Hose Routing and Flat Mount Dropouts and with eyelets for Mud Guards
Rear Shock	N/A
Headset	FSA No. 42 Integrated Road, 1 1/2" lower and 1 1/8" upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 28 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless with Black Brass Nipples
Rims	Whyte Disc Road 20mm Deep, 20mm Wide, Offset Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyres	Schwalbe S-ONE, 700 x 30c, 30-622
Shift Levers	Shimano ST-4700 Tiagra, 10 Speed
Front Derailleur	Shimano FD-4700 Tiagra, 10 Speed
Rear Derailleur	Shimano RD-4700 Tiagra, 10 Speed
Cassette	Shimano CS-4700 Tiagra 11-32, 10 Speed
Chain	FSA Team Issue, 10 Speed
Crankset	FSA Omega 34-50, 10 Speed, Compact Double
Bottom Bracket	FSA Mega Exo, 68mm
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 1pcs 3d Forged 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Road, 31.8mm, Compact "Wing" Bar
Stem	Whyte -6 Deg/6 Deg, 100mm 52cm, 110mm 54cm/56cm, 120mm 58cm
Grips	Whyte Anti Slip with 3M Reflective logos on tapes
Front Brakes	TRP HyRd, Flat Mount, Linear outer cables with Kevlar Reinforcement, 160mm Rotor, Internal Routing
Rear Brakes	TRP HyRd, Flat Mount, Linear outer cables with Kevlar Reinforcement, 160mm Rotor, Internal Routing
Brake Levers	Shimano ST-4700 Tiagra
Pedals	Fibre Reinforced Composite Platform

The Dorset benefits from Shimano's 10-speed Tiagra groupset, with a wide-ratio cassette to make getting up the hills a breeze. On the descents, reliable TRP Flat Mount disc brakes will slow you down.

Whether you're commuting longer distances, winter training or entering summer sports, the Whyte Road Disc range offers Cyclo Cross durability with pure Road geometry.

A strong alloy 6061 frame, with mudguard and rack eyelets, combined with wide section Offset Rimmed RD-7 rims and TRP Hydro/Mechanical disc brakes will give years of reliable all-season performance.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	10.3Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
52	72.5	74	540	271.5	781.5
54	73	73.5	555	271.5	798.5
56	73	73	570	271.5	814.5
58	73	73	585	271.5	830.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
52	998.4	425	27.2	145	520
54	1003.3	425	27.2	160	540
56	1012.8	425	27.2	175	560
58	1027.8	425	27.2	190	580

DEVON

COMPACT-FIT

Sports Road/Commuter Disc - RD7 Series

SRP £1,060



Colour	Matt Granite with Magenta/Blue
Sizes Available	47,49,51,53
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Flat Mount 160 Chainstay Disc mount
Fork	Straight Bladed Carbon Front Fork, Tapered Alloy Steerer with Internal Hose Routing and Flat Mount Dropouts and with eyelets for Mud Guards
Rear Shock	N/A
Headset	FSA No. 42 Integrated Road, 1 1/2" lower and 1 1/8" upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 28 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless with Black Brass Nipples
Rims	Whyte Disc Road 20mm Deep, 20mm Wide, Offset Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyres	Schwalbe S-ONE, 700 x 30c, 30-622
Shift Levers	Shimano ST-4700 Tiagra, 10 Speed
Front Derailleur	Shimano FD-4700 Tiagra, 10 Speed
Rear Derailleur	Shimano RD-4700 Tiagra, 10 Speed
Cassette	Shimano HG-500 11-32, 10 Speed
Chain	FSA Team Issue, 10 Speed
Crankset	FSA Omega 32-48, 10 Speed, 172.5mm Crank Length, Compact Double
Bottom Bracket	FSA Mega Exo, 68mm
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 3D Forged 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Road, 31.8mm, Compact "Wing" Bar
Stem	Whyte -6 Deg/6 Deg, 80mm 47cm/49cm, 90mm 51cm, 100mm 53cm
Grips	Whyte Anti Slip with 3M Reflective logos on tapes
Front Brakes	TRP HyRd, Flat Mount, Linear outer cables with Kevlar Reinforcement, 160mm Rotor, Internal Routing
Rear Brakes	TRP HyRd, Flat Mount, Linear outer cables with Kevlar Reinforcement, 160mm Rotor, Internal Routing
Brake Levers	Shimano ST-4700 Tiagra
Pedals	Fibre Reinforced Composite Platform

Compact geometry makes for a more comfortable female-focused fit. The Devon's TRP HyRd disc brakes use an innovative hybrid cable/hydraulic system to provide powerful braking whatever the conditions.

A strong alloy 6061 frame, with mudguard and rack eyelets combined with wide section offset rimmed RD-7 wheels will give years of reliable all-season performance.

Whether you're commuting longer distances, winter training or entering summer sports, the Whyte Road Disc range offers Cyclo Cross durability with Road geometry.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	10.2Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
47	71.5	75	507	269	721
49	72	74.5	515	271.5	742.5
51	72.5	74	525	271.5	776.5
53	73	73.5	535	271.5	793.5

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
47	984.8	425	27.2	115	470
49	985	425	27.2	130	490
51	985.4	425	27.2	145	510
53	985.4	425	27.2	160	530

SUFFOLK

Sports Road/Commuter Disc - RD7 Series

SRP £1,350



Colour	Matt Granite with Orange/Aqua
Sizes Available	52,54,56,58
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Internal Cable Routing with DOX, Flat Mount, 160 Chainstay Disc mount.
Fork	Straight Bladed Carbon Front Fork, Tapered Alloy Steerer with Internal Hose Routing and Flat disc mount and eyelets for Mud Guards
Rear Shock	N/A
Headset	FSA No. 42 Integrated Road, 1 1/2" lower and 1 1/8" upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole, 11 Speed
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 28 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless with Black Brass Nipples
Rims	Whyte Disc Road 20mm Deep, 20mm Wide, Offset Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyres	Maxxis Rouler TR, Tubeless Ready, 700 x 28c, Black/Grey, with Maxxshield Puncture Protection, Folding
Shift Levers	Shimano 105 ST-505, Full Hydraulic brake lever, 11 Speed
Front Derailleur	Shimano 105, 11 Speed
Rear Derailleur	Shimano 105, 32T Max Capacity, 11 Speed
Cassette	Shimano 105, 11-32, 11 Speed
Chain	Shimano CN-600, 11 Speed
Crankset	FSA Gossamer Pro EVO-386 DB 34-50, 11 Speed, Compact Double
Bottom Bracket	FSA EVO-8681, 68mm
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 3D Forged 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom Road, Triple Panel Design
Bar	Whyte Road, 31.8mm, Compact "Wing" Bar
Stem	Whyte -6 Deg, 100mm 52cm, 110mm 54cm/56cm, 120mm 58cm
Grips	Whyte Anti Slip with 3M Reflective logos on tapes
Front Brakes	Shimano BR-785 Hydraulic, 160mm Rotor, Internal Routing
Rear Brakes	Shimano BR-785 Hydraulic, 160mm Rotor, Internal Routing
Brake Levers	Shimano ST-505 Hydraulic
Pedals	Fibre Reinforced Composite Platform

The Suffolk benefits from Shimano's 11-speed 105 groupset with full hydraulic brakes. A wide-ratio cassette makes getting up the hills a breeze and the brakes will give you confidence in all weather conditions.

A strong alloy 6061 frame, with mudguard and rack eyelets, combined with wide section RD-7 rims and disc brakes will give years of reliable all-season performance.

Best in Test in the Cycling Plus "Bikes For All Seasons" group test, the Suffolk was described as a "Fantastic all-round road bike with superb hydraulic brakes".

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	9.7Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
52	72.5	74	540	271.5	781.5
54	73	73.5	555	271.5	798.5
56	73	73	570	271.5	814.5
58	73	73	585	271.5	830.5

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
52	998.4	425	27.2	145	520
54	1003.3	425	27.2	160	540
56	1012.8	425	27.2	175	560
58	1027.8	425	27.2	190	580

WHITECHAPEL

Fast Urban/Commuter - R7 Series

SRP £580



Colour	Matt Zinc with Black/Lime
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Custom Whyte Dropouts
Fork	Straight Bladed 6061 T6 Alloy Front Fork with Forged crown, Post mount with Single Eyelets
Rear Shock	N/A
Headset	FSA No. 23 Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	Whyte Disc Road 20mm Deep, 20mm Wide, Offset Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyres	Vittoria Zaffiro, 700 x 32c, Black, with Puncture Protection
Shift Levers	Shimano SL-M370, Altus, 9 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano RD-M3000, Acera, 9 Speed
Cassette	Shimano HG-200-9, 11-34 9 Speed
Chain	KMC 9 Speed
Crankset	Alloy, narrow/wide 42T chainring with Alloy Chain Guard
Bottom Bracket	FSA Square Taper, 68mm
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 1pcs 3D Forged 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte Narrow, 31.8mm, 30mm Rise, 620mm Wide
Stem	Whyte, S,M 60mm L, 70mm XL, 80mm
Grips	Whyte Custom with extra-thick bar plugs
Front Brakes	Tektro Auriga, 160mm Rotor
Rear Brakes	Tektro Auriga, 160mm Rotor, Internal Routing
Brake Levers	Tektro Auriga
Pedals	Fibre Reinforced Composite Platform

The Whitechapel is all about simplicity: a single chain ring and nine gears at the back will give years of urban use, and by placing the disc brake caliper inside the rear triangle, adding mudguards or a rack couldn't be easier.

Based on our high performance mountain bike geometry, all our Fast Urban bikes have a long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent slow speed manoeuvrability.

For 2017 we have a new frame, featuring a brand new front triangle with internal cable routing, BBX and new slimmed down seat stays to give even more comfort.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	10.4Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5	74	567.9	266.5	716.5
M	70	73.5	595.7	266.5	748.5
L	70	73	613	271.5	786
XL	70	73	626.9	271.5	817

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1047.8	420	27.2	145	406.4
M	1079.2	420	27.2	165	444.5
L	1094.1	420	27.2	185	495
XL	1109.3	420	27.2	205	533

CARNABY COMPACT-FIT

Fast Urban/Commuter - R7 Series

SRP £580



Colour	Matt Aqua with Black/Grey
Sizes Available	S,M,L
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Custom Whyte Dropouts
Fork	Straight Bladed 6061 T6 Alloy Front Fork with Forged crown, Post mount with Single Eyelets
Rear Shock	N/A
Headset	FSA No. 23 Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	Whyte Disc Road 20mm Deep, 20mm Wide, Offset Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyres	Vittoria Zaffiro, 700 x 32c, Black, with Puncture Protection
Shift Levers	Shimano SL-M370, Altus, 9 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano Acera RD-M3000, 9 Speed
Cassette	Shimano HG-200-9, 11-34 9 Speed
Chain	KMC, 9 Speed
Crankset	Alloy, narrow/wide 39T chainring with Alloy Chain Guard
Bottom Bracket	FSA Square Taper, 68mm
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 1pcs 3D Forged 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom Women's, Triple Panel Design
Bar	Whyte Narrow, 31.8mm, 30mm Rise, 600mm Wide
Stem	Whyte, S,M 60mm L,70mm
Grips	Whyte Custom with extra-thick bar plugs
Front Brakes	Tektro Auriga 160mm Rotor
Rear Brakes	Tektro Auriga 160mm Rotor, Internal Routing
Brake Levers	Tektro Auriga
Pedals	Fibre Reinforced Composite Platform

The Carnaby is all about simplicity, with the addition of female-focused components such as Whyte's women's specific saddle. Nine gears operated by one shifter will give years of urban use while disc brakes guarantee consistent stopping performance, whatever the weather.

Based on our high performance mountain bike geometry, all our Fast Urban bikes have a long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent slow speed manoeuvrability.

A custom rear dropout allows us to mount the rear hydraulic disc brake caliper inside the rear triangle for easy fitment of a rack or mudguards.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	10.4Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74.5	546.5	266.5	732.5
M	69.5	73.5	572.1	266.5	735.5
L	70	73	598.3	266.5	767.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1040.2	420	27.2	140	393.7
M	1052.2	420	27.2	160	431.8
L	1069.2	420	27.2	180	469.9

SHOREDITCH

Fast Urban/Commuter - R7 Series

SRP £690



Colour	Matt Orange with Black
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Custom Whyte Dropouts
Fork	Straight Bladed Carbon Front Fork with Alloy Steerer Tube, Full Carbon Dropout and eyelet for Mud Guards
Rear Shock	N/A
Headset	FSA No. 23 Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	Whyte Disc Road 20mm Deep, 20mm Wide, Offset Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyres	Vittoria Zaffiro Pro, 700 x 32c, Black, with Puncture Protection, Folding
Shift Levers	Shimano Deore, 10 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano Deore Shadow Plus, 10 Speed
Cassette	Shimano HG-50-10, 11-36 10 Speed
Chain	Shimano HG-54, 10 Speed
Crankset	Alloy, narrow/wide 42T chainring with Guard, 10 Speed
Bottom Bracket	FSA Square Taper, 68mm
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 1pcs 3D Forged 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte Narrow, 31.8mm, 30mm Rise, 620mm Wide
Stem	Whyte, S,M 60mm L, 70mm XL, 80mm
Grips	Whyte Custom with extra-thick bar plugs
Front Brakes	Tektro Auriga, 160mm Rotor
Rear Brakes	Tektro Auriga, 160mm Rotor, Internal Routing
Brake Levers	Tektro Auriga
Pedals	Fibre Reinforced Composite Platform

The Shoreditch employs mountain biking clutch mech technology to ensure the chain stays put no matter how rough the route becomes. Elsewhere, the upgrade to a carbon fork saves weight and smoothes out road chatter.

Based on our high performance mountain bike geometry, all our Fast Urban bikes have a long wheelbase and relaxed head angle for high speed stability and a shorter stem for excellent slow speed manoeuvrability.

A custom rear dropout mounts the hydraulic disc brake caliper inside the rear triangle, clearing the way for any rack or mudguards that may be required. 1 by 10 MTB gearing promises years of reliable urban use and hydro discs guarantee consistent performance in all conditions.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	10.2Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5	74	567.9	266.5	716.5
M	70	73.5	595.7	266.5	748.5
L	70	73	613	271.5	786
XL	70	73	626.9	271.5	817
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1047.8	420	27.2	145	406.4
M	1079.2	420	27.2	165	444.5
L	1094.1	420	27.2	185	495
XL	1109.3	420	27.2	205	533

VICTORIA COMPACT-FIT

Fast Urban/Commuter - R7 Series

SRP £799



Colour	Matt Granite with Grey/Magenta
Sizes Available	S,M,L
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Custom Whyte Dropouts
Fork	Straight Bladed Carbon Front Fork, with Post Mount and Single Eyelets
Rear Shock	N/A
Headset	FSA No. 23 Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	Whyte Disc Road 20mm Deep, 20mm Wide, Offset Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyres	Maxxis Rouler, 700 x 28c, Folding Black/Grey, with Maxxshield Puncture Protection
Shift Levers	Shimano Sora SL-R3000, 9 Speed
Front Derailleur	Shimano Sora FD-R3000, 9 Speed
Rear Derailleur	Shimano Sora RD-R3000, 9 Speed
Cassette	Shimano HG-200, 11-32 9 Speed
Chain	Shimano HG-53, 9 Speed
Crankset	Shimano FC-R345-L, Double 50-34, 9 Speed, Octalink
Bottom Bracket	Shimano, Octalink BB-ES300, 68mm
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 1pcs 3D Forged 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Narrow, 31.8mm, 30mm Rise, 600mm Wide
Stem	Whyte, 60mm S, 70mm M, 80mm L
Grips	Whyte double Density, Lock-on
Front Brakes	Tektro Auriga 160mm Rotor
Rear Brakes	Tektro Auriga 160mm Rotor, Internal Routing
Brake Levers	Tektro Auriga
Pedals	Fibre Reinforced Composite Platform

A lightweight aluminium frame employs compact geometry to make this bike perfect for shorter riders who want a wide-ratio 2x9spd Shimano drivetrain.

A custom rear dropout allows us to mount the rear hydraulic disc brake caliper inside the rear triangle, clearing the way for any rack or mudguards that may be required.

Our shaped, butted and uniquely profiled rear stays give all our fast urban bikes a fantastically responsive and comfortable ride.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	10.1Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74.5	546.5	266.5	732.5
M	69.5	73.5	572.1	266.5	735.5
L	70	73	598.3	266.5	767.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1040.2	420	27.2	140	393.7
M	1052.2	420	27.2	160	431.8
L	1069.2	420	27.2	180	469.9

PORTOBELLO

Fast Urban/Commuter - R7 Series

SRP £799



Colour	Matt Granite with Grey/Lime
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Custom Whyte Dropouts
Fork	Straight Bladed Carbon Front Fork, with Post Mount and Single Eyelets
Rear Shock	N/A
Headset	FSA No. 23 Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	Whyte Disc Road 20mm Deep, 20mm Wide, Offset Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyres	Vittoria Zaffiro Pro, 700 x 28c, Black, with Puncture Protection, Folding
Shift Levers	Shimano Sora SL-R3000, 9 Speed
Front Derailleur	Shimano Sora FD-R3000, 9 Speed
Rear Derailleur	Shimano Sora RD-R3000, 9 Speed
Cassette	Shimano HG-200, 11-32 9 Speed
Chain	KMC CN-HG53, 9 Speed
Crankset	Shimano FC-R345-L, Double 50-34, 9 Speed, Octalink
Bottom Bracket	Shimano, Octalink BB-ES300, 68mm
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 1pc 3D Forged 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Narrow, 31.8mm, 20mm Rise, 620mm Wide
Stem	Whyte, 70mm S, 80mm M, 90mm L & XL
Grips	Whyte Custom Dual Density Lock-on
Front Brakes	Tektro Auriga, 160mm Rotor
Rear Brakes	Tektro Auriga, 160mm Rotor, Internal Routing
Brake Levers	Tektro Auriga
Pedals	Fibre Reinforced Composite Platform

A lightweight aluminium frame employs compact geometry to make this bike perfect for shorter riders who want a wide-ratio 2x9spd Shimano drivetrain.

The Portobello features a carbon fork to smooth out the road chatter and dropout eyelets to allow our custom mud guards to be fitted.

A custom rear dropout allows us to mount the rear hydraulic disc brake caliper inside the rear triangle, clearing the way for any rack or mudguards that may be required.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	10.2Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5	74	567.9	266.5	716.5
M	70	73.5	595.7	266.5	748.5
L	70	73	613	271.5	786
XL	70	73	626.9	271.5	817
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1047.8	420	27.2	145	406.4
M	1079.2	420	27.2	165	444.5
L	1094.1	420	27.2	185	495
XL	1109.3	420	27.2	205	533

CAMBRIDGE

Fast Urban/Commuter - R7 Series

SRP £899



Colour	Matt Zinc with Grey/Blue
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Custom Whyte Dropouts
Fork	Straight Bladed Carbon Front Fork with Alloy Steerer Tube, Full Carbon Dropout and eyelet for Mud Guards
Rear Shock	N/A
Headset	FSA No. 23 Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
Rims	Whyte Disc Road 20mm Deep, 20mm Wide, Offset Sleeved Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyres	Vittoria Zaffiro Pro, 700 x 32c, Black, with Puncture Protection, Folding
Shift Levers	SRAM APEX 1, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM Apex 1, 11 Speed
Cassette	SRAM PG-1130, 11-42, 11 Speed
Chain	SRAM PC-1110, 11 Speed
Crankset	SRAM FC350, XSYNC 42T, 11 Speed
Bottom Bracket	SRAM GXP, 68mm
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 1pcs 3D Forged 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Narrow, 31.8mm, 30mm Rise, 620mm Wide
Stem	Whyte, 70mm S, 80mm M, 90mm L & XL
Grips	Whyte Custom Dual Density Lock-on's
Front Brakes	Tektro Auriga 160mm Rotor
Rear Brakes	Tektro Auriga 160mm Rotor, Internal Routing
Brake Levers	Tektro Auriga
Pedals	Fibre Reinforced Composite Platform

We were excited to be able to spec SRAM's new Apex 1 road groupset on the Cambridge. With its 1 by 11 wide range 11-42T drivetrain, it will help you conquer even the hilliest of cities.

Based on our high performance mountain bike geometry, all our Fast Urban bikes have a long wheelbase and relaxed head angle for high speed stability, with a shorter stem for excellent slow speed manoeuvrability.

For 2017 we have a brand new frame, featuring a new front triangle with BBX internal cable routing and new slimmed down seat stays to give even more comfort.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	10.0Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5	74	567.9	266.5	716.5
M	70	73.5	595.7	266.5	748.5
L	70	73	613	271.5	786
XL	70	73	626.9	271.5	817
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1047.8	420	27.2	145	406.4
M	1079.2	420	27.2	165	444.5
L	1094.1	420	27.2	185	495
XL	1109.3	420	27.2	205	533

PIMLICO

Fast Urban/Commuter - R7 Series

SRP £899



Colour	Matt Magenta with Grey/Black
Sizes Available	S,M,L
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	Straight Bladed Carbon Front Fork with Alloy Steerer Tube, Full Carbon Dropout and eyelet for Mud Guards
Rear Shock	N/A
Headset	FSA No. 23 Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
Rims	Whyte Disc Road 20mm Deep, 20mm Wide, Offset Sleeved Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyres	Maxxis Rouler, 700 x 28c, Black/Grey, with Maxxshield Puncture Protection, Folding
Shift Levers	SRAM Via Centro, 10 Speed
Front Derailleur	SRAM Via Centro, 10 Speed
Rear Derailleur	SRAM Via Centro, 10 Speed
Cassette	SRAM PG-1030, 11-32, 10 Speed
Chain	SRAM PC-1031, 10 Speed
Crankset	SRAM Via Centro, 48-32, 10 Speed, Compact
Bottom Bracket	SRAM Power Spline, 68mm
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 1pcs 3D Forged 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom Women's Fit, Triple Panel Design
Bar	Whyte Narrow, 31.8mm, 20mm Rise, 580mm Wide
Stem	Whyte, 70mm XS & S, 80mm M
Grips	Whyte double Density, Lock-on
Front Brakes	Tektro Auriga 160mm Rotor
Rear Brakes	Tektro Auriga 160mm Rotor, Internal Routing
Brake Levers	Tektro Auriga WS
Pedals	Fibre Reinforced Composite Platform

A lightweight aluminium frame employs compact geometry to make this bike a perfect fit for female riders, while a carbon fork does a great job of dampening out road buzz.

Based on our high performance mountain bike geometry, the Pimlico has a long wheelbase and relaxed head angle for high speed stability, a shorter stem for excellent slow speed manoeuvrability and slightly shorter and lower top tube to fit a woman's physique better.

The Pimlico takes advantage of SRAM's Via Centro groupset, specifically designed for urban riding with optimised ratios and slightly wider Q factor for a little more heel clearance.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	10.3Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74.5	546.5	266.5	732.5
M	69.5	73.5	572.1	266.5	735.5
L	70	73	598.3	266.5	767.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1040.2	420	27.2	140	393.7
M	1052.2	420	27.2	160	431.8
L	1069.2	420	27.2	180	469.9

STIRLING

Fast Urban/Commuter - R7 Series

SRP £1,060



Colour	Matt Granite with Grey/Orange
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	Straight Bladed Carbon Front Fork with Alloy Steerer Tube, Full Carbon Dropout and eyelet for Mud Guards
Rear Shock	N/A
Headset	FSA No. 23 Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 28 Hole
Spokes	DT Champion, 2.0mm Black Stainless with Brass Nipples
Rims	Whyte Disc Road 20mm Deep, 20mm Wide, Offset Sleeved Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyres	Maxxis Rouler, 700 x 28c, Black/Grey, with Maxxshield Puncture Protection, Folding
Shift Levers	SRAM S700, 11 Speed
Front Derailleur	SRAM Rival 22, 11 Speed
Rear Derailleur	SRAM Rival 22, 11 Speed
Cassette	SRAM PG-1130, 11-32, 11 Speed
Chain	SRAM PC-1130, 11 Speed
Crankset	SRAM Rival 22, 50-34 Compact, 11 Speed
Bottom Bracket	SRAM GXP XR, 68mm
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 3D Forged 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Narrow, 31.8mm, 30mm Rise, 620mm Wide
Stem	Whyte, 70mm S, 80mm M, 90mm L & XL
Grips	Whyte double Density, Lock-on
Front Brakes	Tektro Gemini, 160mm Rotor
Rear Brakes	Tektro Gemini, 160mm Rotor, Internal Routing
Brake Levers	Tektro Gemini
Pedals	Fibre Reinforced Composite Platform

The Stirling is our top of the range aluminium urban bike, boasting Tektro's powerful Gemini disc brakes and SRAM's superb Rival 22 flat bar drivetrain.

Based on our high performance mountain bike geometry, the Stirling has a long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent slow speed manoeuvrability.

For 2017 we have a brand new frame, which features a brand new front triangle with BBX internal cable routing and new slimmed down seat stays to give even more comfort.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	9.9Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5	74	567.9	266.5	716.5
M	70	73.5	595.7	266.5	748.5
L	70	73	613	271.5	786
XL	70	73	626.9	271.5	817

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1047.8	420	27.2	145	406.4
M	1079.2	420	27.2	165	444.5
L	1094.1	420	27.2	185	495
XL	1109.3	420	27.2	205	533

MONTPELLIER

Fast Urban/Commuter - R7 Series

SRP £1,599



Colour	Matt Granite with Metallic Brass
Sizes Available	M,L,XL
Frame	Full Carbon Monocoque with tapered headtube and internal cable routing and Full Carbon Dropouts
Fork	Straight Bladed Carbon Front Fork with Alloy Steerer Tube, Full Carbon Dropout and eyelet for Mud Guards
Rear Shock	N/A
Headset	FSA No. 42 Integrated Road, 1 1/8" upper Sealed Cartridge Bearing, 1.5 lower Sealed Cartridge Bearing
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, XD Driver, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 28 Hole
Spokes	DT Champion 2.0mm, Black Stainless with Brass Nipples
Rims	Whyte Disc Road 20mm Deep, 20mm Wide, Offset Sleeved Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyres	Maxxis Rouler, 700 x 28c, Black/Grey, with Maxxshield Puncture Protection, Folding
Shift Levers	SRAM S700, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM Rival 1, Long Cage, 11 Speed
Cassette	SRAM PG-1150, 10-42, 11 Speed
Chain	SRAM PC-1130, 11 Speed
Crankset	SRAM S350, XSYNC 44T chainring, 175mm Crank Length
Bottom Bracket	SRAM GXP Team, 68mm
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 3D Forged 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Narrow, 31.8mm, Riser Bar 30mm, 620mm Wide
Stem	Whyte, 80mm M, 90mm L & XL
Grips	Whyte, Dual Density
Front Brakes	Tektro Gemini, 160mm Rotor
Rear Brakes	Tektro Gemini, 160mm Rotor, Internal Routing
Brake Levers	Tektro Gemini
Pedals	None

Whyte's latest carbon technology comes to the urban market, combined with SRAM's Rival 1 by 11 groupset, it creates one of the lightest and most progressive Urban bikes available today.

We have incorporated our "Oversize/Undersize" approach from our carbon hardtails to give great power delivery away from the lights, but with class-leading comfort.

Based on our high performance mountain bike geometry, the Montpellier bridges the gap between out-right road speed and MTB control, with its long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent slow speed manoeuvrability.

Dropout Code	DROPWHRD
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	8.9Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	70	73.5	597	271.5	744
L	70	73	616.1	271.5	776
XL	70	73	623.3	271.5	804.1
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1069.1	420	27.2	140	444.5
L	1084	420	27.2	160	495
XL	1099.1	420	27.2	180	533

HIGHGATE E-BIKE

COMPACT-FIT

SHIMANO
STEPS

Fast Urban/Commuter STEPS e-Bike - eR7 Series

SRP: £2,150



Colour	Matt Granite with Grey/Magenta
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Tapered Head Tube, Custom Drawn, Multi Butted with Custom Whyte Dropouts and Kick Stand mount
Fork	Straight Bladed Carbon Front Fork with Post Mount and Single Eyelets, Internal Cable Route
Rear Shock	N/A
Headset	FSA No. 42 B CUP for 1 1/8" upper and 1.5" lower
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	Whyte Disc Road 20mm Deep, 20mm Wide, Offset Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyres	Vittoria Zaffiro Pro, 700 x 32c, Black, with Puncture Protection, Folding
Shift Levers	Shimano SL-M610, Deore, 10-Speed With STEP's SC-E6010 Display
Front Derailleur	N/A
Rear Derailleur	Shimano RD-M615, Deore, 10-Speed, Shadow Plus
Cassette	Shimano CS-HG50, 10-SPEED 11-36T
Chain	Shimano CN-E6090-10, e-Bike
Crankset	Crankarms for Shimano STEPS, 44T with Double Sided chain guard, 10 Speed
Bottom Bracket	STEP's Drive Unit E-6001 with Speed Sensor and Magnet
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 1pcs 3D Forged 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte Narrow, 31.8mm, 20mm Rise, 620mm Wide
Stem	Whyte, S,M 60mm L, 70mm XL, 80mm
Grips	Whyte Custom Lock-on
Front Brakes	Tektro Auriga, 160mm Rotor
Rear Brakes	Tektro Auriga, 160mm Rotor, Internal Routing
Brake Levers	Tektro Auriga
Pedals	Fibre Reinforced Composite Platform

Using Shimano's STEPS e-Bike Drive Unit the Highgate is able to take advantage of the pedal assist without compromising the weight distribution and therefore the handling of this compact fit bike.

Our custom built e-Bike frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot, continuous outer cables that keep the gear shifts working smoother for longer and optional custom matched mud guards. The Highgate also features a carbon fork to smooth out the road chatter.

The ride-feel of these e-Bikes is second to none, with a fantastic quality lightweight frame which includes our uniquely shaped rear seat stays for comfort and performance.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	17.3Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	70	74.5	546.5	276.5	765.5
M	70	73.5	572.1	276.5	795.5
L	70	73	598.3	276.5	822.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1100	450	27.2	140	393.7
M	1115.2	450	27.2	160	431.8
L	1130.3	450	27.2	180	469.9

Shimano Steps	Battery Info Volts:- 36 volts and 11.6ah, giving 418 watt hours. Range:- 37miles in High, 52miles in Normal and 77miles in Eco. Watts:- 250 watts continuous output, Maximum output 500 watts Torque 50NM in high & 30 NM in eco.
----------------------	--

CLIFTON E-BIKE

Fast Urban/Commuter STEPS e-Bike - eR7 Series

SRP £2,150

SHIMANO
STEPS



Colour	Matt Granite with Grey/Blue
Sizes Available	M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Tapered Head Tube, Custom Drawn, Multi Butted with Custom Whyte Dropouts and Kick Stand mount
Fork	Straight Bladed Carbon Front Fork, with Post Mount and Single Eyelets, Internal Cable Route
Rear Shock	N/A
Headset	FSA No. 42 B CUP for 1 1/8" upper and 1.5" lower
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	Whyte Disc Road 20mm Deep, 20mm Wide, Offset Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyres	Vittoria Zaffiro Pro, 700 x 32c, Black, with Puncture Protection, Folding
Shift Levers	Shimano SL-M610, Deore, 10-Speed With STEP's SC-E6010 Display
Front Derailleur	N/A
Rear Derailleur	Shimano RD-M615, Deore, 10-Speed, Shadow Plus
Cassette	Shimano CS-HG50, 10-SPEED 11-36T
Chain	Shimano CN-E6090-10, e-Bike
Crankset	Crankarms for Shimano STEPS, 44T with Double Sided chain guard, 10 Speed
Bottom Bracket	STEP's Drive Unit E-6001 with Speed Sensor and Magnet
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 1pcs 3D Forged 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte Narrow, 31.8mm, 20mm Rise, 620mm Wide
Stem	Whyte, S,M 60mm L, 70mm XL, 80mm
Grips	Whyte Custom Lock-on
Front Brakes	Tektro Auriga, 160mm Rotor
Rear Brakes	Tektro Auriga, 160mm Rotor, Internal Routing
Brake Levers	Tektro Auriga
Pedals	Fibre Reinforced Composite Platform

Using Shimano's STEPS e-Bike Drive Unit the Clifton is able to take advantage of the pedal assist without compromising the weight distribution and therefore the handling.

Our custom built e-Bike frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot, continuous outer cables that keep the gear shifts working smoother for longer and optional custom matched mud guards. The Clifton also features a carbon fork to smooth out the road chatter.

The ride-feel of these e-Bikes is second to none, with a fantastic quality lightweight frame which includes our uniquely shaped rear seat stays for comfort and performance. This bike is the slickest way to ride around the city for work or pleasure.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	17.3Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5	74	567.9	276.5	765.5
M	70	73.5	595.7	276.5	795.5
L	70	73	613	276.5	822.5
XL	70	73	625.4	276.5	851.5

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1100	450	27.2	145	406.4
M	1115.2	450	27.2	165	444.5
L	1130.3	450	27.2	185	495
XL	1145	450	27.2	205	533.4

Shimano Steps	Battery Info Volts:- 36 volts and 11.6ah, giving 418 watt hours. Range:- 37miles in High, 52miles in Normal and 77miles in Eco. Watts:- 250 watts continuous output, Maximum output 500 watts Torque 50NM in high & 30 NM in eco.
---------------	---

FAIRFIELD

All Terrain/Leisure - C7 Series

SRP £530



Colour	Matt Granite with Grey/Lime
Sizes Available	S,M,L
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and concealed rear brake post
Fork	6061 Alloy, curved blade with Alloy Steerer and Eyelets
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Silver Stainless with Brass Nipples
Rims	WTB DX-17 700c, 32 Hole
Tyres	Maxxis Roamer 700 x 42c with Kevlar Puncture Protection
Shift Levers	Shimano Altus SL-M310, 8 Speed
Front Derailleur	Shimano Tourney FD-TY710, 8 Speed
Rear Derailleur	Shimano Altus RD-M360, 8 Speed
Cassette	Shimano CS-HG-31, 11-32, 8 Speed
Chain	Shimano HG-40, 8 Speed
Crankset	Shimano M311, 48-38-28, 8 Speed
Bottom Bracket	Square Taper, 68mm
Seatpost	Whyte 20mm Offset, 30.9mm, 6061 Alloy, 2 bolt clamp
Seat	Whyte Custom, triple panel design
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Ergo Dual Density Lock-on's
Front Brakes	Tektro Forged V Brake
Rear Brakes	Tektro Forged V Brake
Brake Levers	Tektro Ergo Style brake lever with Integrated Bell
Pedals	Alloy Body with Non Slip Grip

The Fairfield is where Whyte's idea of a 29" wheel MTB design dovetails with classic European-style trekking bike. With a lightweight, comfortable chassis and a full Shimano drivetrain, it will give years of unrivalled performance.

Our custom built frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot that stops water spray from the rear wheel getting into the frame. Our bikes are also mud guard ready for all year use.

The ride-feel of these bikes is second to none, with a fantastic quality lightweight frame including our unique rear seat stays which really improve the comfort and performance, whatever the terrain.

Dropout Code	DROPWHLC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	11.8Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74	592	278	765
M	69	73.5	617	278	774
L	69	73	632	278	805
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1100.6	435	30.9	115	457
M	1120.5	435	30.9	125	495
L	1130.6	435	30.9	135	546

FAIRFIELD WOMEN'S

All Terrain/Leisure - C7 Series

SRP £530



Colour	Matt Granite with Grey/Gold
Sizes Available	S,M,L
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and concealed rear brake post
Fork	6061 Alloy, curved blade with Alloy Steerer and Eyelets
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Silver Stainless with Brass Nipples
Rims	WTB DX-17 700c, 32 Hole
Tyres	Maxxis Roamer 700 x 42c with Kevlar Puncture Protection
Shift Levers	Shimano Altus SL-M310, 8 Speed
Front Derailleur	Shimano Tourney FD-TY710, 8 Speed
Rear Derailleur	Shimano Altus RD-M360, 8 Speed
Cassette	Shimano CS-HG-31, 11-32, 8 Speed
Chain	Shimano HG-40, 8 Speed
Crankset	Shimano M311, 48-38-28, 8 Speed
Bottom Bracket	Square Taper, 68mm
Seatpost	Whyte 20mm Offset, 30.9mm, 6061 Alloy, 2 bolt clamp
Seat	Whyte Custom Women's Fit, triple panel design
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Ergo Dual Density Lock-on's
Front Brakes	Tektro Forged V Brake
Rear Brakes	Tektro Forged V Brake
Brake Levers	Tektro Ergo Style brake lever with Integrated Bell
Pedals	Alloy Body with Non Slip Grip

The Fairfield is where Whyte's idea of a 29" wheel MTB design dovetails with classic European-style trekking bike. With a lightweight, comfortable chassis and a full Shimano drivetrain, it will give years of unrivalled performance.

All the same key design features as the unisex version, with the added benefit of a partially dropped top tube. This increases stand over height, while still keeping enough room inside the frame to comfortably fit a water bottle.

Another benefit of the partially dropped tube is the maintained stiffness of the frame (fully dropped top tube frames are flexi and offer less steering control). Puncture resistant tyres offer extra reliability and piece of mind.

Dropout Code	DROPWHLC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	11.8Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68	74.5	570	278	718
M	69	74	587	278	737
L	69	73.5	612	278	756.9
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1082.9	435	30.9	107	431.8
M	1095.4	435	30.9	115	457
L	1105.4	435	30.9	125	495

RIDGEWAY

All Terrain/Leisure - C7 Series

SRP £625



Colour	Matt Orange with Grey/Black
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Custom Whyte Dropouts
Fork	SR Suntour NEX HLO, 63mm travel, Hydro Lockout
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with eyelets
Tyres	WTB All Terrain Comp 700 x 35c with Flat Guard
Shift Levers	Shimano Altus SL-M370, 9 Speed
Front Derailleur	Shimano Altus FD-M370, 9 Speed
Rear Derailleur	Shimano Altus RD-M370, 9 Speed
Cassette	Shimano HG-200-9, 11-32, 9 Speed
Chain	KMC CN-HG-53, 9 Speed
Crankset	Shimano M371, 48-36-26, 9 Speed
Bottom Bracket	Square Taper, 68mm
Seatpost	Whyte 20mm Offset, 30.9mm, 6061 Alloy, With 2 Bolt Clamp
Seat	Whyte Custom, triple panel design
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 80mm S, 90mm M & L
Grips	Whyte Custom Ergo Dual Density Lock-on's
Front Brakes	Tektro Auriga, 160mm Rotor
Rear Brakes	Tektro Auriga, 160mm Rotor, Internal Routing
Brake Levers	Tektro Auriga
Pedals	Fibre Reinforced Composite Platform

With hydraulic disc brakes and a comfort enhancing suspension fork, the Ridgeway is ready for adventure whenever you are. Its lightweight, comfortable chassis and full Shimano drivetrain will give years of unrivalled performance.

Our custom built frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot that stops water spray from the rear wheel getting into the frame and the continuous outer cables that are internally routed to keep the gear shifts working smoother for longer.

The ride-feel of these bikes is second to none, with a fantastic quality lightweight frame including our unique rear seat stays which really improve the comfort and performance, whatever the terrain. Puncture resistant tyres offer extra reliability and piece of mind.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	13.3Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74	592	278	765
M	69	73.5	617	278	774
L	69	73	632	278	805
XL	69	73	646	278	854
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1100.6	435	30.9	115	457
M	1120.5	435	30.9	125	495
L	1130.6	435	30.9	135	546
XL	1145.5	435	30.9	145	585

RIDGEWAY WOMEN'S

All Terrain/Leisure - C7 Series

SRP £625



Colour	Matt Magenta with Black/Blue
Sizes Available	S,M,L
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Custom Whyte Dropouts
Fork	SR Suntour NEX HLO, 63mm travel with Hydro Lockout
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with eyelets
Tyres	WTB All Terrain Comp 700 x 35c with Flat Guard
Shift Levers	Shimano Altus SL-M370, 9 Speed
Front Derailleur	Shimano Altus FD-M370, 9 Speed
Rear Derailleur	Shimano Altus RD-M370, 9 Speed
Cassette	Shimano HG-200-9, 11-32, 9 Speed
Chain	KMC CN-HG-53, 9 Speed
Crankset	Shimano M371, 48-36-26, 9 Speed
Bottom Bracket	Square Taper, 68mm
Seatpost	Whyte 20mm Offset, 30.9mm, 6061 Alloy, 2 bolt clamp
Seat	Whyte Custom Women's Fit, triple panel design
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Ergo Dual Density Lock-on's
Front Brakes	Tektro Auriga, 160mm Rotor
Rear Brakes	Tektro Auriga, 160mm Rotor, Internal Routing
Brake Levers	Tektro Auriga
Pedals	Fibre Reinforced Composite Platform

With hydraulic disc brakes and a comfort enhancing suspension fork, the Ridgeway is ready for adventure whenever you are. Its lightweight, comfortable women's specific chassis and full Shimano drivetrain will give years of unrivalled performance.

All the same key design features as the unisex version, with the added benefit of a partially dropped top tube. This increases stand over height, while still keeping enough room inside the frame to comfortably fit a water bottle.

Another benefit of the partially dropped tube is the maintained stiffness of the frame (fully dropped top tube frames are flexi and offer less steering control). Puncture resistant tyres give extra reliability and piece of mind.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	13.5Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68	74.5	570	278	718
M	69	74	587	278	737
L	69	73.5	612	278	756.9
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1082.9	435	30.9	107	431.8
M	1095.4	435	30.9	115	457
L	1105.4	435	30.9	125	495

CALEDONIAN

All Terrain/Leisure - C7 Series

SRP £849



Colour	Matt Zinc with Grey/Blue
Sizes Available	S,M,L
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted Internal Cable Routing with BBX and Custom Whyte Dropouts
Fork	SR Suntour NCX-D LO, 63mm travel, Coil Spring, Hydro Lockout and Alloy Steerer tube
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Stainless Steel with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with eyelets
Tyres	Vittoria Randonneur Trail 700 x 35c, with Double Shielding puncture protection
Shift Levers	Shimano Deore, 10 Speed
Front Derailleur	Shimano Deore, 10 Speed
Rear Derailleur	Shimano LX T670, 10 Speed
Cassette	Shimano Deore, CS-HG-500, 11-34, 10 Speed
Chain	Shimano HG-54, 10 Speed
Crankset	Shimano T521, 48-36-26, Octalink, Hollow Tech, 10 Speed
Bottom Bracket	Shimano ES-300 Octalink, 68mm
Seatpost	Whyte 20mm Offset, 30.9mm, 6061 Alloy, 2 bolt clamp
Seat	Whyte Custom, triple panel design
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 80mm S, 90mm M & L
Grips	Whyte Custom Ergo Dual Density Lock-on's
Front Brakes	Shimano M447, 160mm Rotor
Rear Brakes	Shimano M447, 160mm Rotor, Internal Routing
Brake Levers	Shimano M445
Pedals	Fibre Reinforced Composite Platform

With wide ratio gearing taken from Shimano's rugged mountain bike line and high quality Vittoria trail tyres, the Caledonian is primed for a big adventure.

Our custom built frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot that stops water spray from the rear wheel getting into the frame and the continuous outer cables that are internally routed to keep the gear shifts working smoother for longer.

The ride-feel of these bikes is second to none, with a fantastic quality lightweight frame including our unique rear seat stays which really improve the comfort and performance, whatever the terrain.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	13.1Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74	592	278	765
M	69	73.5	617	278	774
L	69	73	632	278	805
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1100.6	435	30.9	115	457
M	1120.5	435	30.9	125	495
L	1130.6	435	30.9	135	546

CALEDONIAN WOMEN'S

All Terrain/Leisure - C7 Series

SRP £849



Colour	Matt Granite with Lime/Magenta
Sizes Available	S,M,L
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Custom Whyte Dropouts
Fork	SR Suntour NCX-D LO Lite, 63mm travel, Coil Spring, Hydro Lockout and Alloy steerer tube
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Stainless Steel with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with eyelets
Tyres	Vittoria Randonneur Trail 700 x 35c, with Double Shielding puncture protection
Shift Levers	Shimano Deore, 10 Speed
Front Derailleur	Shimano Deore, 10 Speed
Rear Derailleur	Shimano LX T670, 10 Speed
Cassette	Shimano Deore, CS-HG-500, 11-34, 10 Speed
Chain	Shimano HG-54, 10 Speed
Crankset	Shimano T521, 48-36-26, Octalink, Hollow Tech, 10 Speed
Bottom Bracket	Shimano ES-300 Octalink, 68mm
Seatpost	Whyte 20mm Offset, 30.9mm, 6061 Alloy, 2 bolt clamp
Seat	Whyte Custom Women's Fit, triple panel design
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Ergo Dual Density Lock-on's
Front Brakes	Shimano M447, 160mm Rotor
Rear Brakes	Shimano M447, 160mm Rotor, Internal Routing
Brake Levers	Shimano M445
Pedals	Fibre Reinforced Composite Platform

With wide ratio gearing taken from Shimano's rugged mountain bike line and high quality Vittoria trail tyres, the Caledonian is primed for a big adventure.

All the same key design features as the Unisex version, with the added benefit of a partially dropped top tube. This increases stand over height, while still keeping enough room inside the frame to comfortably fit a water bottle.

Another benefit of the partially dropped tube is the maintained stiffness of the frame (fully dropped top tube frames are more flexible and offer less steering control).

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	13.1Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68	74.5	570	278	718
M	69	74	587	278	737
L	69	73.5	612	278	756.9
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1082.9	435	30.9	107	431.8
M	1095.4	435	30.9	115	457
L	1105.4	435	30.9	125	495

CONISTON E-BIKE

All Terrain/Leisure STEPS e-Bike - eC7 Series

SRP £2,150

SHIMANO
STEPS



Colour	Matt Granite with Grey/Blue
Sizes Available	S,M,L
Frame	6061 Hydro Formed T6 Aluminium, Tapered Head Tube, Custom Drawn, Multi Butted with Custom Whyte Dropouts and Kick Stand mount
Fork	SR Suntour NCX-D LO, 63mm travel, Alloy Tapered Steerer tube, Coil Spring and Hydro Lockout
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, Sealed Cartridge Bearing 1.5" Lower, 1 1.8" Caged Upper Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Sandvik Stainless Steel with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with eyelets
Tyres	Vittoria Randonneur Trail 700 x 35c, with Double Shielding puncture protection
Shift Levers	Shimano SL-M610 Deore, 10 Speed With STEP's SC-E6010 Display
Front Derailleur	N/A
Rear Derailleur	Shimano RD-T670 SLX, 10 Speed
Cassette	Shimano HG-500-10, 11-34, 10 Speed
Chain	Shimano STEP's E6090, e-Bike Specific, 10 Speed
Crankset	Shimano STEP's E-6000, 44T with Double Sided chain guard, 10 Speed
Bottom Bracket	STEP's Drive Unit E-6001 with Speed Sensor and Magnet
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 bolt clamp
Seat	Whyte Custom, triple panel design
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Ergo Dual Density Lock-on
Front Brakes	Shimano M425, 160mm Rotor
Rear Brakes	Shimano M425, 160mm Rotor, Internal Routing
Brake Levers	Shimano M395
Pedals	Fibre Reinforced Composite Platform

Using Shimano's STEPS e-Bike Drive Unit the Coniston is able to take advantage of the pedal assist without compromising the weight distribution and therefore the handling.

Our custom built e-Bike frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot, continuous outer cables that keep the gear shifts working smoother for longer and optional custom matched mud guards.

The ride-feel of these e-Bikes is second to none, with a fantastic quality lightweight frame which includes our uniquely shaped rear seat stays for comfort and performance, plus Whyte's very own take on All Terrain geometry.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	20.5Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5	74	591	288	767
M	70	73.5	617.6	288	821
L	70	73	637.8	288	825
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1107	445	30.9	115	406.4
M	1123.3	445	30.9	125	444.5
L	1138.3	445	30.9	135	495.3

Shimano Steps	Battery Info Volts:- 36 volts and 11.6ah, giving 418 watt hours. Range:- 37miles in High, 52miles in Normal and 77miles in Eco. Watts:- 250 watts continuous output, Maximum output 500 watts Torque 50NM in high & 30 NM in eco.
----------------------	--

CONISTON WOMEN'S E-BIKE

All Terrain/Leisure STEPS e-Bike - eC7 Series

SRP £2,150

SHIMANO
STEPS



Colour	Matt Granite with Grey/Magenta
Sizes Available	S,M,L
Frame	6061 Hydro Formed T6 Aluminium, Tapered Head Tube, Custom Drawn, Multi Butted with Custom Whyte Dropouts and Kick Stand mount
Fork	SR Suntour NCX-D LO, 63mm travel, Alloy Tapered Steerer tube, Coil Spring and Hydro Lockout
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, Sealed Cartridge Bearing 1.5" Lower, 1 1.8" Caged Upper Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Sandvik Stainless Steel with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with eyelets
Tyres	Vittoria Randonneur Trail 700 x 35c, with Double Shielding puncture protection
Shift Levers	Shimano SL-M610 Deore, 10 Speed With STEP's SC-E6010 Display
Front Derailleur	N/A
Rear Derailleur	Shimano SLX M675, 10 Speed
Cassette	Shimano Deore HG-62, 11-34, 10 Speed
Chain	Shimano STEP's E6090, e-Bike Specific, 10 Speed
Crankset	Shimano STEP's E-6000, 44T with Double Sided chain guard, 10 Speed
Bottom Bracket	STEP's Drive Unit E-6000 with Speed Sensor and Magnet
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 bolt clamp
Seat	Whyte Custom, triple panel design
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Ergo Dual Density Lock-on
Front Brakes	Shimano M425, 160mm Rotor
Rear Brakes	Shimano M425, 160mm Rotor, Internal Routing
Brake Levers	Shimano M395
Pedals	Fibre Reinforced Composite Platform

Using Shimano's STEPS e-Bike Drive Unit the Coniston is able to take advantage of the pedal assist without compromising the weight distribution and therefore the handling.

Our custom built e-Bike frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot, continuous outer cables that keep the gear shifts working smoother for longer and optional custom matched mud guards.

The ride-feel of these e-Bikes is second to none, with a fantastic quality lightweight frame which includes our uniquely shaped rear seat stays for comfort and performance plus Whyte's very own take on All Terrain geometry.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	19.8Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68	74.5	557	288	716
M	69	74	584	288	748
L	69	73.5	590	288	768
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1093	445	30.9	107	406.4
M	1106	445	30.9	115	444.5
L	1126	445	30.9	125	495.3

Shimano Steps	Battery Info Volts:- 36 volts and 11.6ah, giving 418 watt hours. Range:- 37miles in High, 52miles in Normal and 77miles in Eco. Watts:- 250 watts continuous output, Maximum output 500 watts Torque 50NM in high & 30 NM in eco.
----------------------	--

STRAWBERRY HILL

Lightweight Classic/Leisure

SRP £640



Colour	Matt Granite with Gold/Grey
Sizes Available	S,M,L
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted with Internal Cable Routing and BBX and Custom Whyte Dropouts with Kick Stand mount.
Fork	Whyte Alloy, curved blade with Alloy Steerer
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Silver Stainless with Brass Nipples
Rims	Whyte Double Walled Alloy, 700c, 32 Hole
Tyres	Maxxis Roamer, 700 x 42c High Air Volume, with Kevlar Puncture Guard
Shift Levers	Shimano Altus SL-M370, 9 Speed
Front Derailleur	Shimano Altus FD-M370, 9 Speed
Rear Derailleur	Shimano Acera RD-T3000, 9 Speed
Cassette	Shimano HG-30, 11-34, 9 Speed
Chain	KMC, 9 Speed
Crankset	Shimano M391 Acera, 48-36-26
Bottom Bracket	Square Taper, 68mm
Seatpost	Whyte 20mm Offset, 6061 Alloy, 30.9mm, 2 Bolt Clamp
Seat	Whyte Custom Women's Fit, triple panel design
Bar	Whyte Swept Bar, 25.4mm, 600mm Wide, 45mm Sweep
Stem	Whyte Custom, High Rise, 20 Deg
Grips	Ergon, Single Density For Swept Bar
Front Brakes	Tektro Forged V Brake
Rear Brakes	Tektro Forged V Brake
Brake Levers	Tektro V Brake Levers with Integrated Bell
Pedals	Alloy Body with Non Slip Grip

Whyte's take on a stylish, comfortable, lifestyle bike. Combining the elegance of a vintage machine with a 27 speed drivetrain and a remarkably lightweight frame, we've made it even easier to get up the hills, or just to lift up the stairs when you get home.

Comfort was given top priority with the Strawberry Hill. The Whyte saddle is highly cushioned but also lightweight. The grips are specifically designed to fit your palm on a swept handle bar and even the brake levers have a Kraton insert to add a tactile and comfortable feel.

Full mudguards, a chainset cover, kick stand, and internal cable routing keep all the moving parts away from the rider.

Dropout Code	DROPWHLC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	12.9Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68	74.5	537.3	288	663
M	69	74	563	288	686
L	69	73.5	586.8	288	677
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1066	445	30.9	130	431.8
M	1079.8	445	30.9	160	457
L	1099.8	445	30.9	180	495